

Cap Test Gauge

- Aluminum hardcoat
- Rocker lug swivel
- Petcock to release pressure
- Used for testing hose or static pressures on hydrants or trucks
- Supplied with 0-300 PSI glycerine filled 3½" diameter gauge

NH (NST) Thread	Dixon Part #
1½"	AFC150F-TGWP
2½"	AFC250F-TGWP



Other sizes and threads are also available. Consult the factory for price and availability.

Three Way Gauge Valve

- Brass body, rubber disc
- Permits the checking or replacing of a gauge without shutting down the whole line
- Working pressure: **175 PSI**

NPT Thread	Dixon Part #
¼"	TWGV25



Sprinkler System Gauges (UL-393)



- Specifically designed for the fire sprinkler industry
- Bourdon tube pressure gauges with black polycarbonate case
- Snap-in clear polycarbonate window, 4" face
- White aluminum dial with stop pin, black and red markings
- Black aluminum non-adjustable pointer
- ¼" NPT lower mount
- ASME B40.1 Grade B (+ 3/2/3% accuracy)
- UL Listed (UL-393) and FM Approved for fire sprinkler service
- Ambient Temperature Range: **-40°F to 140°F**

Type	PSI Range	Dixon Part #
Water	0 - 300	SWG300-4
Air	0-80	SWRG80-250-4
Water Retard	0-250	




Straight Ball Drip Valves

This valve is designed to drain the low point of a system. It should be placed between the fire department connection and the swing check valve.

- Will seal automatically under pressure
- Install in the horizontal position only
- Working pressure: **175 PSI**

Male NPT	Male NPT	Dixon Part #	Powhatan Part #
½"	½"	SBDV50	23-148-00001
¾"	¾"	SBDV75	23-148-00002



Angled Ball Drip Valves

Male NPT	Male NPT	Dixon Part #	Powhatan Part #
½"	½"	ASBDV50	23-181-00001
¾"	¾"	ASBDV75	23-181-00002

