

HT-Series ISO16028 Flushface Interchange (Coupler)



(Female Thread)

HT-Series

Part Number	Body Size	Thread Size	Body Material	Weight (lb)	List Price	Bag Qty	Pack Qty
3HTF3	3/8"	3/8"-18 NPTF	steel	0.44	\$68.61	5	25
3HTF3-SS	3/8"	3/8"-18 NPTF	316 SS	0.44	209.36	5	25
3HTOF3	3/8"	9/16"-18 ORB	steel	0.49	70.95	5	25
3HTBF3	3/8"	G3/8" BSPP	steel	0.44	67.41	5	25
3HTBF3-SS	3/8"	G3/8" BSPP	316 SS	0.44	209.36	5	25
3HTF4	3/8"	1/2"-14 NPTF	steel	0.48	68.61	5	25
3HTF4-SS	3/8"	1/2"-14 NPTF	316 SS	0.48	209.36	5	25
3HTOF4	3/8"	3/4"-16 ORB	steel	0.53	74.88	5	25
3HTBF4	3/8"	G1/2" BSPP	steel	0.48	67.41	5	25
3HTBF4-SS	3/8"	G1/2" BSPP	316 SS	0.48	209.36	5	25
4HTF4	1/2"	1/2"-14 NPTF	steel	0.86	77.02	---	20
4HTF4-SS	1/2"	1/2"-14 NPTF	316 SS	0.86	230.21	---	20
4HTOF4	1/2"	3/4"-16 ORB	steel	0.86	76.56	---	20
4HTBF4	1/2"	G1/2" BSPP	steel	0.86	75.65	---	20
4HTBF4-SS	1/2"	G1/2" BSPP	316 SS	0.86	240.19	---	20
4HTOF5	1/2"	7/8"-14 ORB	steel	0.92	79.75	---	20
4HTF6	1/2"	3/4"-14 NPTF	steel	0.98	85.53	---	20
4HTF6-SS	1/2"	3/4"-14 NPTF	316 SS	0.98	252.20	---	20
4HTOF6	1/2"	1-1/16"-12 ORB	steel	0.96	84.00	---	20
4HTBF6	1/2"	G3/4" BSPP	steel	0.98	84.00	---	20
4HTBF6-SS	1/2"	G3/4" BSPP	316 SS	0.98	247.51	---	20
5HTOF5	5/8"	7/8"-14 ORB	steel	1.58	109.80	---	10
5HTF6	5/8"	3/4"-14 NPTF	steel	1.51	106.48	---	10
5HTF6-SS	5/8"	3/4"-14 NPTF	316 SS	1.51	329.29	---	10
5HTOF6	5/8"	1-1/16"-12 ORB	steel	1.49	109.80	---	10
5HTBF6	5/8"	G3/4" BSPP	steel	1.51	104.58	---	10
5HTBF6-SS	5/8"	G3/4" BSPP	316 SS	1.51	329.28	---	10
6HTF6	3/4"	3/4"-14 NPTF	steel	1.82	148.15	---	10
6HTF6-SS	3/4"	3/4"-14 NPTF	316 SS	1.82	474.73	---	10
6HTOF6	3/4"	1-1/16"-12 ORB	steel	1.91	147.59	---	10
6HTBF6	3/4"	G3/4" BSPP	steel	1.82	142.96	---	10
6HTBF6-SS	3/4"	G3/4" BSPP	316 SS	1.82	474.73	---	10
6HTF8	3/4"	1"-11 1/2 NPTF	steel	2.06	156.33	---	10
6HTF8-SS	3/4"	1"-11 1/2 NPTF	316 SS	2.06	503.20	---	10
6HTOF8	3/4"	1-5/16"-12 ORB	steel	2.16	155.02	---	10
6HTBF8	3/4"	G1" BSPP	steel	2.06	156.33	---	10
6HTBF8-SS	3/4"	G1" BSPP	316 SS	2.06	503.20	---	10
8HTF8	1"	1"-11 1/2 NPTF	steel	2.67	247.72	---	10
8HTF8-SS	1"	1"-11 1/2 NPTF	316 SS	2.67	831.07	---	10
8HTOF8	1"	1-5/16"-12 ORB	steel	2.68	247.48	---	10
8HTBF8	1"	G1" BSPP	steel	2.67	243.20	---	10
8HTBF8-SS	1"	G1" BSPP	316 SS	2.67	785.85	---	10
8HTF10	1"	1-1/4"-11 1/2 NPTF	steel	2.75	246.06	---	10
8HTF10-SS	1"	1-1/4"-11 1/2 NPTF	316 SS	2.75	152.10	---	10
8HTOF10	1"	1-5/8"-12 ORB	steel	2.84	751.63	---	10
8HTBF10	1"	G1-1/4" BSPP	steel	2.75	260.55	---	10
8HTBF10-SS	1"	G1-1/4" BSPP	316 SS	2.75	271.61	---	10

HT-Series ISO16028 Flushface Interchange (Coupler)



(Male Thread)

Part Number	Body Size	Thread Size	Body Material	Weight (lb)	List Price	Bag Qty	Pack Qty
3HTM3	3/8"	3/8"-18 NPTF	steel	0.46	\$72.28	5	25
3HTM4	3/8"	1/2"-14 NPTF	steel	0.48	72.28	5	25
3HTOM4	3/8"	3/4"-16 ORB	steel	0.48	73.89	5	25
3HTJM4	3/8"	3/4"-16 JIC	steel	0.47	74.36	5	25
3HTJB4	3/8"	3/4"-16 JIC Bulkhead	steel	0.64	84.03	5	25
4HTM4	1/2"	1/2"-14 NPTF	steel	0.97	81.22	---	20
5HTM6	5/8"	3/4"-14 NPTF	steel	1.53	123.05	---	10
6HTM6	3/4"	3/4"-14 NPTF	steel	1.98	158.21	---	10
6HTM8	3/4"	1"-11 1/2 NPTF	steel	2.18	166.45	---	10
8HTM8	1"	1"-11 1/2 NPTF	steel	2.58	263.36	---	10
8HTM10	1"	1-1/4"-11 1/2 NPTF	steel	2.80	271.72	---	10



Attention Required!

Although a special lubricant is used to protect the flushface seals during pre-service storage, the seals are still vulnerable until they are exposed to the system fluid.

It is recommended to lubricate the seals before the first connection by placing a drop of oil into the main valve grooves on the face of the nipple.