HT-Series ISO16028 Flushface Interchange (Nipple)

Part	Body	Thread	Body	Weight	List	Bag	Pack
Number	Size	Size	Material	(lb)	Price	Qty	Qty
HT3F3	3/8"	3/8"-18 NPTF	steel	0.27	\$25.35	5	25
HT3F3-SS	3/8"	3/8"-18 NPTF	316 SS	0.27	\$25.35	5	25 25
HT3OF3	3/8"	9/16"-18 ORB	steel	0.27	24.88	5	25
HT3BF3	3/8"	G3/8" BSPP	steel	0.34	24.88	5	25
HT3BF3-SS	3/8"	G3/8" BSPP	316 SS	0.27	92.01	5	25
HT3F4	3/8"	1/2"-14 NPTF	steel	0.27	25.35	5	25
HT3F4-SS	3/8"	1/2"-14 NPTF	316 SS	0.31	82.41	5	25
HT3OF4	3/8"	3/4"-16 ORB	steel	0.35	25.19	5	25
HT3BF4	3/8"	G1/2" BSPP	steel	0.31	24.88	5	25
HT3BF4-SS	3/8"	G1/2" BSPP	316 SS	0.31	82.43	5	25
HT4F4	1/2"	1/2"-14 NPTF	steel	0.42	45.33		20
HT4F4-SS	1/2"	1/2"-14 NPTF	316 SS	0.42	140.19		20
HT4OF4	1/2"	3/4"-16 ORB	steel	0.40	47.29		20
HT4BF4	1/2"	G1/2" BSPP	steel	0.42	44.52		20
HT4BF4-SS	1/2"	G1/2" BSPP	316 SS	0.42	140.19		20
HT4OF5	1/2"	7/8"-14 ORB	steel	0.43	47.63		20
HT4F6	1/2"	3/4"-14 NPTF	steel	0.53	47.63		20
HT4F6-SS	1/2"	3/4"-14 NPTF	316SS	0.53	147.22		20
HT4OF6	1/2"	1-1/16"-12 ORB	steel	0.58	47.57		20
HT4BF6	1/2"	G3/4" BSPP	steel	0.53	47.57		20
HT4BF6-SS	1/2"	G3/4" BSPP	316 SS	0.53	147.22		20
HT5OF5	5/8"	7/8"-14 ORB	steel	0.90	58.41		10
HT5F6	5/8"	3/4"-14 NPTF	steel	0.95	58.75		10
HT5F6-SS	5/8"	3/4"-14 NPTF	316 SS	0.95	188.24		10
HT5OF6	5/8"	1-1/16"-12 ORB	steel	1.02	58.41		10
HT5BF6	5/8"	G3/4" BSPP	steel	0.95	52.93		10
HT5BF6-SS	5/8"	G3/4" BSPP	316 SS	0.95	188.24		10
HT6F6	3/4"	3/4"-14 NPTF	steel	1.00	94.92		10
HT6F6-SS	3/4"	3/4"-14 NPTF	316 SS	1.00	303.96		10
HT6OF6	3/4"	1-1/16"-12 ORB	steel	1.02	96.05		10
HT6BF6	3/4"	G3/4" BSPP	steel	1.00	92.53		10
HT6BF6-SS	3/4"	G3/4" BSPP	316 SS	1.00	303.96		10
HT6F8	3/4"	1"-11 1/2 NPTF	steel	1.15	94.68		10
HT6F8-SS	3/4"	1"-11 1/2 NPTF	316 SS	1.15	319.14		10
HT6OF8	3/4"	1-5/16"-12 ORB	steel	1.12	99.44		10
HT6BF8	3/4"	G1" BSPP	steel	1.15	94.68		10
HT6BF8-SS	3/4"	G1" BSPP	316 SS	1.15	319.14		10
HT8F8	1"	1"-11 1/2 NPTF	steel	1.69	135.44		10
HT8F8-SS	1"	1"-11 1/2 NPTF	316 SS	1.69	384.36		10
HT8OF8	1"	1-5/16"-12 ORB	steel	1.65	141.99		10
HT8BF8	1"	G1" BSPP	steel	1.69	132.02		10
HT8BF8-SS	1"	G1" BSPP	316 SS	1.69	384.36		10
HT8F10	1"	1-1/4"-11 1/2 NPTF	steel	1.84	137.87		10
HT8F10-SS	1"	1-1/4"-11 1/2 NPTF	316 SS	1.84	423.56		10
HT8OF10	1"	1-5/8"-12 ORB	steel	1.93	146.94		10
HT8BF10	1"	G1-1/4" BSPP	steel	1.84	137.87		10
HT8BF10-SS	1"	G1-1/4" BSPP	316 SS	1.84	417.21		10



(Female Thread)

HT-Series ISO16028 Flushface Interchange (Nipple)

-866

I Free:

Good

sa

Part Number	Body Size	Thread Size	Body Material	Weight (lb)	List Price	Bag Qty	Pack Qty
HT3M3	3/8"	3/8"-18 NPTF	steel	0.31	\$27.14	5	25
HT3M4	3/8"	1/2"-14 NPTF	steel	0.38	27.14	5	25
HT3OM4	3/8"	3/4"-16 ORB	steel	0.37	29.18	5	25
HT3JM4	3/8"	3/4"-16 JIC	steel	0.37	30.08	5	25
HT3JB4	3/8"	3/4"-16 JIC Bulkhead	steel	0.45	36.47	5	25
HT4M4	1/2"	1/2"-14 NPTF	steel	0.42	49.20		20
HT5M6	5/8"	3/4"-14 NPTF	steel	0.92	58.02		10
HT6M6	3/4"	3/4"-14 NPTF	steel	1.00	99.94		10
HT6M8	3/4"	1"-11 1/2 NPTF	steel	1.08	100.99		10
HT8M8	1"	1"-11 1/2 NPTF	steel	1.73	144.25		10
HT8M10	1"	1-1/4"-11 1/2 NPTF	steel	1.86	148.00		10

Although a special lubricant is used to protect the flushface seals during pre-service storage, the seals are still vulnerable until they are exposed to the system fluid.

It is recommended to lubricate the seals before the first connection by placing a drop of oil into the main valve grooves on the face of the nipple.

Ca

GOO



(Male Thread)



-4

oduc



om

