

EA-Series Water-Blast Interchange


- 'Maxi-Latch' retention system maximizes nipple retention while reducing incidents of brinneling.
- Nipple mounted sleeve guard protects against accidental disconnection.
- Smooth bore full-flow design ensures maximum flow with minimal pressure drop.
- Heavy duty knurled sleeves with locking pin provide maximum protection against brinneling and accidental disconnection.
- Steel body components maximize service life by resisting the effects of brinneling and internal erosion.



| Performance Specifications | Operating Bar (PSI) | Min. Burst Bar (PSI) | Flow Rate $\Delta P=1$ Bar | Locking Mechanism |
|----------------------------|---------------------|----------------------|----------------------------|-------------------|
| 1/2" | 700 (10,000) | 2,069 (30,000) | 227 LPM (60 GPM) | Maxi-Latch |
| 'EA' Series Interchange | Parker | Aeroquip | Snap-Tite | --- |
| 1/2" | Series 'WB' | FD69 | 56-Series | --- |

EA-Series Water-Blast Interchange (Coupler)


| Part Number | Body Size | Thread Size | Body Material | Weight (lb) | List Price | Bag Qty | Pack Qty |
|-------------|-----------|--------------|---------------|-------------|----------------|---------|----------|
| 4EAF3 | 1/2" | 3/8"-18 NPTF | steel | 0.68 | \$89.40 | 5 | 25 |
| 4EAF4 | 1/2" | 1/2"-14 NPTF | steel | 0.65 | 89.40 | 5 | 25 |



(Female Thread)

EA-Series Water-Blast Interchange (Nipple)

| Part Number | Body Size | Thread Size | Body Material | Weight (lb) | List Price | Bag Qty | Pack Qty |
|-------------|-----------|--------------|---------------|-------------|----------------|---------|----------|
| EA4F3 | 1/2" | 3/8"-18 NPTF | steel | 0.38 | \$20.85 | 5 | 25 |
| EA4F4 | 1/2" | 1/2"-14 NPTF | steel | 0.34 | 20.85 | 5 | 25 |



(Female Thread)

EA-Series