




DF-Series Industrial Interchange




Body Size	End Size	Female NPT(F)	Female BSPP	Female ORB	Male NPT(F)	Male BSPT	Male ORB	Male JIC 37°	Hose Barb	Push-Loc Barb	Reusable Barb	Max. O.D.	Hex Size
'D' Coupler		Dimension 'A'										'B'	'C'
1/4"	1/8"	51.8mm	-	-	56.1mm	-	-	-	-	-	-	24.9mm	11/16"
1/4"	1/4"	56.1mm	56.1mm	-	59.4mm	59.4mm	-	-	73.7mm	70.1mm	70.9mm	24.9mm	11/16"
1/4"	5/16"	-	-	-	-	-	-	-	73.7mm	-	-	24.9mm	-
1/4"	3/8"	60.5mm	60.5mm	-	59.9mm	59.9mm	-	-	73.7mm	70.4mm	72.4mm	24.9mm	13/16"
3/8"	1/4"	61.0mm	-	-	65.8mm	-	-	-	76.2mm	-	-	30.0mm	7/8"
3/8"	3/8"	64.0mm	64.0mm	-	69.3mm	69.3mm	-	-	76.3mm	71.7mm	-	30.0mm	7/8"
3/8"	1/2"	71.1mm	-	-	74.7mm	-	-	-	76.3mm	-	-	30.0mm	1"
1/2"	3/8"	75.9mm	-	-	79.5mm	-	-	-	89.2mm	-	-	34.0mm	1-1/16"
1/2"	1/2"	85.3mm	85.3mm	-	80.5mm	80.5mm	-	-	89.2mm	84.1mm	-	34.0mm	1-1/16"
1/2"	3/4"	86.6mm	-	-	82.0mm	-	-	-	89.2mm	-	-	34.0mm	1-3/16"
3/4"	1/2"	74.9mm	-	-	74.9mm	-	-	-	93.7mm	-	-	48.3mm	1-3/16"
3/4"	3/4"	75.9mm	-	-	74.9mm	-	-	-	93.7mm	-	-	48.3mm	1-5/16"
3/4"	1"	80.8mm	-	-	79.2mm	-	-	-	99.8mm	-	-	48.3mm	1-9/16"

'F' Coupler		Dimension 'D'										'E'	'F'
1/4"	1/8"	46.5mm	46.5mm	-	50.0mm	-	-	-	64.3mm	-	-	22.4mm	3/4"
1/4"	1/4"	51.8mm	51.8mm	-	51.8mm	51.8mm	-	-	64.3mm	58.9mm	61.7mm	22.4mm	3/4"
1/4"	5/16"	-	-	-	-	-	-	-	64.3mm	-	-	22.4mm	3/4"
1/4"	3/8"	54.4mm	-	-	52.8mm	-	-	-	72.6mm	58.9mm	63.8mm	22.4mm	13/16"
3/8"	1/4"	57.2mm	-	-	62.2mm	-	-	-	72.6mm	-	-	26.9mm	7/8"
3/8"	3/8"	63.0mm	63.0mm	-	62.5mm	62.5mm	-	-	72.6mm	73.2mm	-	26.9mm	7/8"
3/8"	1/2"	66.3mm	-	-	63.5mm	-	-	-	88.7mm	-	-	26.9mm	1"
1/2"	3/8"	73.7mm	-	-	75.4mm	-	-	-	88.7mm	-	-	30.2mm	1"
1/2"	1/2"	77.2mm	77.2mm	-	78.0mm	78.0mm	-	-	88.7mm	87.9mm	-	30.2mm	1"
1/2"	3/4"	79.8mm	-	-	79.3mm	-	-	-	88.7mm	-	-	30.2mm	1-3/16"

Nipple		Dimension 'G'										'H'	'J'
1/4"	1/8"	36.6mm	-	-	39.9mm	-	-	-	-	-	-	16.5mm	9/16"
1/4"	1/4"	42.2mm	42.2mm	-	42.9mm	42.9mm	-	-	53.1mm	53.1mm	54.9mm	20.1mm	11/16"
1/4"	5/16"	-	-	-	-	-	-	-	53.1mm	-	-	20.1mm	-
1/4"	3/8"	42.2mm	42.2mm	-	44.5mm	44.5mm	-	-	53.1mm	53.1mm	55.4mm	25.7mm	7/8"
3/8"	1/4"	45.2mm	-	-	46.0mm	-	-	-	56.1mm	-	-	20.1mm	11/16"
3/8"	3/8"	45.2mm	45.2mm	-	47.5mm	47.5mm	-	-	56.1mm	55.1mm	-	25.7mm	7/8"
3/8"	1/2"	49.3mm	-	-	51.6mm	-	-	-	56.1mm	-	-	29.5mm	1"
1/2"	3/8"	53.3mm	-	-	55.6mm	-	-	-	64.3mm	-	-	25.7mm	7/8"
1/2"	1/2"	57.1mm	57.1mm	-	59.4mm	59.4mm	-	-	64.3mm	67.6mm	-	29.5mm	1"
1/2"	3/4"	58.4mm	-	-	63.5mm	-	-	-	64.3mm	-	-	34.8mm	1-3/16"
3/4"	1/2"	56.4mm	-	-	60.5mm	-	-	-	76.2mm	-	-	38.6mm	1-5/16"
3/4"	3/4"	56.4mm	-	-	60.5mm	-	-	-	76.2mm	-	-	38.6mm	1-5/16"
3/4"	1"	61.2mm	-	-	65.0mm	-	-	-	82.3mm	-	-	45.7mm	1-9/16"

USC-Series Universal Safety Coupler



Body Size	End Size	Female NPT(F)	Female BSPP	Female ORB	Male NPT(F)	Male BSPT	Male ORB	Male JIC 37°	Hose Barb	Push-Loc Barb	Reusable Barb	Max. O.D.	Hex Size
Coupler		Dimension 'A'										'B'	'C'
1/4"	1/4"	58.0mm	-	-	73.0mm	-	-	-	-	-	-	24.0mm	3/4"
3/8"	3/8"	65.0mm	-	-	-	-	-	-	-	-	-	30.0mm	7/8"

Dimensions