

## Above Ground Petroleum Tank Accessories

Bayco brand accessories are rugged, reliable products which have serviced the petroleum industry for over 20 years.

### Locking Fill Caps and Collars

For above ground fuel tanks. Aluminum or bronze caps come with leather gasket; aluminum, bronze or zinc collars with set screw and lug for padlock. *Order cap and collar separate.* Collar threads to pipe and is secured with a set screw. Side lug for padlocking cap to collar.



Part #	Size	Description
<b>250A</b>	2½"	fill cap, aluminum
<b>250B *</b>	2½"	fill cap, bronze
<b>350A *</b>	3½"	fill cap, aluminum
<b>350B *</b>	3½"	fill cap, bronze
<b>350BC *</b>	3½"	fill cap, bronze, heavy duty
<b>400A</b>	4"	fill cap, aluminum
<b>400B</b>	4"	fill cap, bronze
<b>400BC *</b>	4"	fill cap, bronze, heavy duty
<b>250AC *</b>	2½"	collar, aluminum
<b>250BC</b>	2½"	collar, bronze
<b>350C *</b>	3½"	collar, zinc
<b>350HD *</b>	3½"	collar, zinc, heavy duty
<b>400C</b>	4"	collar, zinc
<b>400HD</b>	4"	collar, zinc, heavy duty
<b>G2500L</b>	2½"	replacement leather gasket for fill cap
<b>G350L</b>	3½"	replacement leather gasket for fill cap
<b>G400L</b>	4"	replacement leather gasket for fill cap

\* Items will be discontinued as stock is depleted.

### Automatic Pressure/Vacuum Relief Caps

- Normally closed, stops fuel evaporation and airborne contaminants
- Lockable
- Relieves both pressure and vacuum buildup in fuel tanks
- Two styles available, choose for stationary or mobile fuel storage tanks as listed below

#### For stationary fuel tanks



Part #	Description
<b>2000L</b>	2" male NPS, relieves vacuum at .7 Hg (.33 PSI) and pressure at 2 PSI, 20 SCFM flow
<b>2500L</b>	2½" male NPS, relieves vacuum at .7 Hg (.33 PSI), and pressure at 2 PSI, 20 SCFM flow
<b>2500RW</b>	removal wrench for PV caps

#### For mobile fuel tanks



Part #	Description
<b>200-PV-9</b>	2" male NPT, relieves vacuum relief at 1" Hg (.5 psig), and pressure at between 7.5 and 9 psig

**SAFETY**  
**ALERT**

**Note:** Bayco brand pressure/vacuum relief caps should be routinely inspected to ensure correct operation and that the relieving components are free to move and the air flow path is not blocked.

### Standard Vent Cap



(Does not have pressure or vacuum valves)

- Allows venting of tank to atmosphere at all times
- Aluminum body
- Male NPS inlet

Part #	Size
<b>2500SFV</b>	2½"