## Station Vents · Cast aluminum construction Part # Description Screws included 47-48 For 11/2" to 2" vapor stack Built-in screen 49 For 3" vapor stack Suction Deflector · Cast aluminum construction Part # Size • Threads to 2" suction pipe 2" A38 4" Twin Lever Fill Cap For use with underground tank fill adaptor Part # Size Bronze body with lockable 400TFLC2BR 4" bronze levers Includes Buna gasket 4" Single Action Fill Caps For use with underground tank fill adapter (top seal) Part # Size Lockable, push-pull operation Choice of aluminum or bronze SA4050AL 4" bodv SA4050BZ 4" Bronze cam arms Includes Buna gasket 4" Vapor Caps Special locking cap for underground tank vapor outlet VR4086 and tanker vapor Part # Size valves VR4100 and VR4000 VR4050AL 4" Aluminum & ultra lightweight VR4050PL 4" nylon versions available Orange colored for visibility Underground Tank Collars Short 4" Fill Adapter Standard 4" Fill Adapter Vapor Adapter NPT NPSM NPT Part # Height Material Part # Height Material Part # Height Material Size Size Size BZ4051 3½" 2-3/8" 4" BZ4051S 4" VR4086 3-5/8" 4" bronze bronze bronze 4" BY4051 4" VR4086BY 3-5/8" 31/2" bayloy bayloy Comes with gasket seal Poppeted vapor collar at station Often employed when soil settles vapor outlet around tank and shorter height is Can also be used as vapor valve required on tanker but does not have air interlock mount Low profile design We Ship GOODYEAR Call Toll Free: 1-8

roduct WebSales@GoodvearRu

World Wi

om