High Flow Swing Check Valves

3000 Series Swing Checks

· Cast aluminum bodies with bronze inspection caps.

•

- Safety flapper assembly all flapper assemblies are drilled and pinned and will not come apart.
- Choice of seals: metal-to-metal, Buna or silicone rubber seals. Large cap designs allow flapper repair/rebuild on unit.
- · Choice of models with or without spring loaded flapper.
- · Full flow design flappers swing out of flow path for maximum flow and low resistance.

3" Threaded Ends (NPT)				
Part #	Description	Length		
3000TE	Metal-to-metal seal	7 1/8"		
3000TESP	Metal-to-metal seal and spring loaded flapper	7 1/8"		
3000TEB	Buna rubber seal	7 1/8"		
3000TES	Silicone rubber seal	7 1/8"		
3000TEBSP	Buna seal and spring loaded flapper	7 1/8"		
3000TESSP	Silicone rubber seal and spring loaded flapper	7 1/8"		

3" Square Flanged (TTMA)

Part #	Description	Length
3001SQN	Metal-to-metal seal	6 7/8"
3001SQSP	Metal-to-metal seal and spring loaded flapper	6 7/8"
3001SQB	Buna rubber seal	6 7/8"
3001SQS	Silicone rubber seal	6 7/8"
3001SQBSP	= an an a can a change a carbo a	6 7/8"
3001SQSSP	Silicone rubber seal and spring loaded flapper	6 7/8"

3" Round Flanged (TTMA)

Part #	Description	Length
3000N	Metal-to-metal seal	5 5/8"
3000SP	Metal-to-metal seal and spring loaded flapper	5 5/8"
3000B	Buna rubber seal	5 5/8"
3000S	Silicone rubber seal	5 5/8"
3000BSP	Buna seal and spring loaded flapper	5 5/8"
3000SSP	Silicone rubber seal and spring loaded flapper	5 5/8"

Gaskets can be found on page 11.

Swing Check Manifold Valves

3" high flow swing check valve complete with 2" female NPT port for mounting an air relief valve

Call Toll Free: 1-866-711

Sales@

-4

roduc



