

Vacuum Gauges



- ASME B40.1, Grade B accuracy (+/- 3-2-3 % accuracy)
- ABS plastic case
- Bronze bourdon tube
- Polycarbonate crystal
- Black aluminum pointer
- Brass movement with polyester segment, designed for extended wear.
- Ambient temperature range of **-40°F to 150°F**

2" Face 1/4" Lower Mount				2" Face 1/4" Center Back Mount				2-1/2" Face 1/4" Lower Mount			
Mercury (Hg)	Fig. Inter.	Minor Grad.	Part #	Mercury (Hg)	Fig. Inter.	Minor Grad.	Part #	Mercury (Hg)	Fig. Inter.	Minor Grad.	Part #
30"	5"	.5"	GL105	30"	5"	.5"	GL205	30"	5"	.5"	GL305

Panel Mount Gauges



- Accuracy class: +/- 1% of span
- Material of wetted parts: copper alloy
- Window: acrylic, snap in
- Dial: aluminum, white
- Pointer: aluminum, black, adjustable
- Mounting flange/bracket: rear flange, stainless steel

Stainless Steel

4 1/2" Face

1/4" Lower Mount

PSI	Part #
0-15	4277750-0001
0-30	4277768-0001
0-60	4277776-0001

Standard Dry Gauges

- Polycarbonate crystal
- Black aluminum pointer
- PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.
- Ambient temperature range of **-40°F to +150°F**

- ASME B40.1, Grade B (+/- 3-2-3% accuracy)
- ABS plastic case
- C-shaped bronze safety bourdon tube (**600 PSI** and lower) helical wound bronze safety bourdon tube (**1000 PSI** and higher)



1-1/2" Face 1/8" Center Back Mount			
PSI	Fig. Inter.	Minor Grad.	Part #
0-30	5	.5	GC605
0-60	5	1	GC610
0-100	10	2	GC615
0-160	20	5	GC620
0-200	20	5	GC625

2" Face 1/4" Center Back Mount			
PSI	Fig. Inter.	Minor Grad.	Part #
0-15	1	.5	GC200
0-30	5	.5	GC215
0-60	5	1	GC220
0-100	10	2	GC225
0-160	20	5	GC230
0-200	20	5	GC235
0-300	30	5	GC240

Standard Dry Gauges



- Polycarbonate crystal
- Black aluminum pointer
- PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.
- Ambient temperature range of **-40°F to +150°F**
- ASME B40.1, Grade B (+/- 3-2-3% accuracy)
- ABS plastic case
- C-shaped bronze safety bourdon tube (**600 PSI** and lower) helical wound bronze safety bourdon tube (**1000 PSI** and higher)

2" Face 1/4" Lower Mount			
PSI	Fig. Inter.	Minor Grad.	Part #
0-15	1	.5	GL100
0-30	5	.5	GL115
0-60	5	1	GL120
0-100	10	2	GL125
0-160	20	5	GL130
0-200	20	5	GL135
0-300	30	5	GL140