

RMV[®] Compound, Tygrip Profile, Multi-Plied Spun Polyester

For a "Grade A" grip on incline conveying

- Tygrip profile provides extra gripping power for incline conveying
- Goodyear's RMV[®] compound is FDA/USDA compliant and offers:
 - superior resistance to animal fats, vegetable and mineral oils
 - high resin content offers state-of-the-art Melt-Weld fabrications
- Multi-Plied Spun Polyester carcass with HPC[™] technology increases strength and durability:
 - superior tracking in both directions
 - resistance to edge wicking and curling
 - flexibility over small pulleys
 - excellent adhesions provide improved belt wear
 - Thermo-Flo[™] splicing capabilities

Description	Plies	Working Tension		Approx. OAG		Weight		COF (approx.)	Pulley Dia.		Temp.	
		PIW*	KN/m	in.	mm	Lbs./Sq.ft.	Kg/Sq.m		In.	mm	°F°	C
RMV 100V2 TFw	2	100	18	0.115	2.9	0.67	3.2	0.30	1.5	38	20-180	-7-82

*Elongation less than 2% at specified PIW

Description	Splicing Methods	Recommended Fasteners**		
		Clipper	Alligator	Staple
RMV 100V2 TFw	Finger-over-finger, Finger, Bias Stepped, Skived Bias, Mechanical Fasteners	36SP or UCM36SP	1	62

** Fastener manufacturer should be consulted to review specific belt and application information