

RMV[®] Compound, Z-Belt[™] Profile, Multi-Plied Spun Polyester

For the highest marks in product flow

- Z-Belt profile can carry up to 30% more product:
 - unique, continuous design reduces vibration on return side idlers
 - allows for drainage when transporting wet products without changing profile direction
- Goodyear's RMV compound is FDA/USDA compliant and offers:
 - superior resistance to animal fats, vegetable and mineral oils
 - high resin content offers state-of-the-art Melt-Weld fabrications
- Multi-Plied Spun Polyester carcass with HPC[™] technology increases strength and durability:
 - superior tracking in both directions
 - resistance to edge wicking and curling
 - flexibility over small pulleys
 - excellent adhesions provide improved belt wear
 - Thermo-Flo[™] splicing capabilities

Description	Plies	Working Tension		Approx. OAG		Weight		COF (approx.)	Pulley Dia.		Temp.	
		PIW*	KN/m	in.	mm	Lbs./Sq.ft.	Kg/Sq.m		In.	mm	°F	°C
RMV 150H2 ZFw-1	2	150	26	0.245	6.2	1.08	5.2	0.30	4.0	102	20 - 180	-7 - 82

*Elongation less than 2% at specified PIW

Description	Splicing Methods	Recommended Fasteners**		
		Clipper	Alligator	Staple
RMV 150H2 ZFw-1	Finger-over-finger, Finger, Bias Stepped, Skived Bias, Mechanical Fasteners	36 or UCM36	7	62

** Fastener manufacturer should be consulted to review specific belt and application information