

USPS

Made to deliver

- These hard-working interwoven PVC belts are specially manufactured to meet the rigorous standards of the United States Postal Service

Description	Plies	Working Tension		Approx. OAG		Weight		COF (approx.)	Pulley Dia.		Temp.	
		PIW*	KN/m	in.	mm	Lbs./Sq.ft.	Kg/Sq.m		In.	mm	°F	°C
USPS 120S1 FBb	1	120	21	0.125	3.2	0.66	3.2	0.25	2.5	64	20-180	-7-82
USPS 150S1 FBb	1	150	26	0.170	4.3	0.91	4.4	0.25	4.0	102	20-180	-7-82
USPS 200S1 FBb	1	200	35	0.220	5.6	1.33	6.4	0.25	6.0	152	20-180	-7-82

*Elongation less than 2% at specified PIW

Description	Splicing Methods	Recommended Fasteners**		
		Clipper	Alligator	Staple
USPS 120S1 FBb	Finger, Skived Bias, Mechanical Fasteners	1 or UX1	7	125
USPS 150S1 FBb	Finger, Skived Bias, Mechanical Fasteners	2 or U2	20	125
USPS 200S1 FBb	Finger, Skived Bias, Mechanical Fasteners	4 or U4	27	187

** Fastener manufacturer should be consulted to review specific belt and application information