

# Ruff-Grip Profile

Superior gripping power  
designed to last

- Ruff-Grip profile offers:
  - unique siped ridge provides superior gripping power
  - flexing over pulleys cleans out unwanted material
  - non-marking PVS compound
- Ideal for conveying boxes, plastic, paper, corrugated cardboard and wood
- Innovative HPC™-constructed multi-ply carcass provides:
  - superior tracking in both directions
  - resistance to edge wicking and curling
  - flexibility over small pulleys
  - excellent adhesions on the belt edge
  - Thermo-Flo™ splicing capabilities

Description	Plies	Working Tension		Approx. OAG		Weight		COF (approx.)	Pulley Dia.		Temp.	
		PIW*	KN/m	in.	mm	Lbs./Sq.ft.	Kg/Sq.m		In.	mm	°F	°C
PVS 150H2 RBb	2	150	26	0.310	7.9	1.03	5.0	0.25	2.5	64	20-180	-7-82

\*Elongation less than 2% at specified PIW

Description	Splicing Methods	Recommended Fasteners**		
		Clipper	Alligator	Staple
PVS 150H2 RBb	Finger-over-finger, Finger, Bias Stepped, Skived Bias, Mechanical Fasteners	2 or U2	20	125

\*\* Fastener manufacturer should be consulted to review specific belt and application information