

D8800 Spring-Driven

All series D8800 hose reels are designed for both hydraulic and pneumatic applications.

- Aluminum construction for corrosion resistance and light weight
- Containerized mainspring for safe and simple maintenance
- Adjustable hose guide to pay out and retrieve hose from any direction
- Ratchet lock to stop hose at required length
- Anti lock-out design insures that ratchet will not engage when hose is fully extended
- Permanent lubrication for smooth operation
- Powder coat finish for appearance, corrosion resistance and durability
- For hose rated up to 700 PSI
- Nitrile seals

For dimensions, see page 21



Reels do not include hose.

D8800



Note: Reels are primarily for manual pullout applications with lift height no more than 17ft. Otherwise, please call factory for application assistance. For hose rated up to 700 PSI.

Model	Inlet Hose Fitting (NPT)	Hose Inner Diameter	Hose Capacity		Pressure PSI
			feet	m	
D8814	1/4"	1/4"	60	18.3	700
D8814	3/8"	3/8"	60	18.3	700
D8814	1/2"	1/2"	60	18.3	700
D8816	3/4"	3/4"	50	15.2	700
D8818	1"	1"	30	9.1	700
D8824	1/4"	1/4"	95	24.5	700
D8824	3/8"	3/8"	95	24.5	700
D8824	1/2"	1/2"	95	29.0	700

Reels do not include hose.

SPRING-DRIVEN REELS