

## VPR® Specialty Truck Mount

Rugged steel construction hose reel designed for applications subject to heavy use and shock loads. Ideal for vehicles such as service trucks.

- Double guide-arm support
- Steel construction for long life in industrial applications
- Containerized main spring for safe, easy maintenance
- Adjustable guide arm
- Four roller guide to protect hose
- Brass and stainless steel swivel
- Durable epoxy powder-coat finish
- Ratchet lock and easy tension adjustment
- Hose stops included for all models
- Nitrile seals

TL, TM, TH

Accessories on page 16

For dimensions, see page 22



Note: Hose attachment on reel drum requires female NPSM swivel fitting.

### Hose Specs

Low Pressure (to 300 PSI)	Type: EPDM/SBR tube Red SBR cover Max Temp: 176° F (80°C)
Medium Pressure (to 3000 PSI)	Type: SAE 100 R1 TYPE AT Synthetic Rubber tube & cover Max Temp: 212° F (100°C)
High Pressure (to 5000 PSI)	Type: SAE 100 R2 TYPE AT Synthetic Rubber tube & cover Max Temp: 212° F (100°C)

Other hose types available, consult factory.

Model	Inlet hose fitting (NPT)	Hose Inner Diameter	Length feet	in	Pressure PSI
TL33C	3/8"	3/8"	30	9.1	300
TL35C	3/8"	3/8"	50	15.2	300
TL43C	1/2"	1/2"	30	9.1	300
TL45C	1/2"	1/2"	50	15.2	300
TL40C	1/2"	Without Hose			300
TM33D	3/8"	3/8"	30	9.1	2000
TM35D	3/8"	3/8"	50	15.2	2000
TM43D	1/2"	1/2"	30	9.1	2000
TM45D	1/2"	1/2"	50	15.2	2000
TM40D	1/2"	Without Hose			3000
TH23C	1/4"	1/4"	30	9.1	5000
TH25C	1/4"	1/4"	50	5.2	5000
TH20C	1/4"	Without Hose			5000
TH33C	3/8"	3/8"	30	9.1	4000
TH35C	3/8"	3/8"	50	5.2	4000
TH30C	3/8"	Without Hose			4000