

POLYWIRE® Series K7130 — Heavy wall PVC food & beverage vacuum/transfer hose

**MEETS
3A³
CRITERIA**

**NSF-51 & NSF-61⁴
MATERIAL**

Heavy wall food and beverage grade vacuum/transfer hose with rated working pressures.

Construction:

Crystal clear PVC compound, formulated with ingredients in compliance with applicable FDA¹ requirements, meets USDA², 3A³ and NSF⁴ criteria and California Proposition 65⁵. Reinforced with helically-wound spring steel wire.

Features:

- 29.9" HG vacuum rating
- Spiral wire reinforcement prevents kinking or collapsing . . . hose diameter will not expand under normal rated working pressures
- Crystal clear — allows visual confirmation of product flow
- Glass-smooth interior — reduces material buildup
- Electrogalvanized helical steel wire can be used for static dissipation (see below†)

- Resistant to chemicals (see chemical-resistance chart)
- Compound hardness 73 ±3 Shore "A"
- Self-extinguishing
- Non-marking
- Non-toxic
- Silicone-free
- One-piece lengths
- Special cut piece lengths available through 1" ID size — check with factory

Applications:

- Full vacuum lines
- Industrial vacuum pumps
- Food & beverage dispensing
- Air and water supply lines
- Car wash applications
- Coolant lines
- Air breathing lines
- Pneumatic parts transfer
- Deionized water systems



**CERTIFIED UNDER
STANDARD 51**

Service Temperature Range: +25°F (-4°C) to 150°F (+65°C)

Series K7130 — PVC food & beverage vacuum/transfer hose — crystal clear

Series No.	Size Code	Nominal ID		Nominal OD		Max. Working† Pressure (PSI)		Standard Length Coils	Approx. Wt. per Pkg.	Min. Bend Radius @ 70°F
		(In)	(mm)	(In)	(mm)	@ 70°F (20°C)	@ 122°F (50°C)			
K7130	04	1/4	6.4	.500	12.7	250	80	100 ft.	10 lbs.	1"
K7130	06	3/8	9.5	.625	15.9	150	80	100 ft.	13 lbs.	1 1/2"
K7130	08	1/2	12.7	.813	20.7	150	80	100 ft.	21 lbs.	2"
K7130	10	5/8	15.9	1.000	25.4	150	65	100 ft.	30 lbs.	2 1/2"
K7130	12	3/4	19.1	1.125	28.6	150	65	100 ft.	36 lbs.	3"
K7130	16	1	25.4	1.375	34.9	100	45	100 ft.	44 lbs.	4"
K7130	20	1 1/4	31.8	1.750	44.5	100	50	50 ft.	37 lbs.	5"
K7130	24	1 1/2	38.1	2.000	50.8	100	35	50 ft.	42 lbs.	6"
K7130	32	2	50.8	2.500	63.5	100	35	50 ft.	56 lbs.	8"

† **Note:** Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

‡ **CAUTION:** This product is designed to dissipate static electricity when the metal wire is properly connected to ground, through the fitting or other means.

Compliance Footnotes:

- 1 FDA** — CFR Title 21 Parts 170 to 199.
- 2 USDA** — Chemically suitable for general use in slaughtering, processing, transporting, or storage areas in direct contact with meat or poultry food product prepared under Federal Inspection.
- 3 3A** — Complies with the criteria in 3-A Sanitary Standards for Multiple-use Plastic Materials used as Product Contact Surfaces for Dairy Equipment, Number 20-18 as amended.
- 4 NSF** — Certified under Standard 51, Plastic materials and components used in food equipment. Compound is also certified under Standard NSF-61 for drinking water system components.
- 5 Proposition 65** — Compounds contain no substances designated as hazardous under California Proposition 65.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.