



Series K1154/K1156 —  
General purpose PVC hose

### Construction:

#### Series K1154/K1156

- Tube — Black PVC compound
- Reinforcement — High tensile strength yarn
- Cover — PVC compound, available in two colors:  
K1154 – red & K1156 – blue

### Features:

- Economical, flexible and lightweight . . . all sizes are within UPS weight limits for significant freight savings
- Excellent abrasion resistance
- U. V. and weather resistant
- Non-marking pin-pricked cover
- Silicone-free core and cover
- Complies with RMA's Class B designation for medium/high oil resistance
- One piece packaging, no random lengths

### Applications:

- Transfer of air, water and mild water soluble chemicals
- Ideal for in-plant applications that require an economical general purpose hose
- Excellent air supply line for pneumatic tools and paint spray systems

**Service Temperature Range:** +14°F (-10°C) to 150°F (+65°C)

## Series K1154/K1156 — General purpose PVC hose

Series No.		Size Code	Nominal ID		Nominal OD		Max. Working† Pressure (PSI)		Standard Length		Approx. Wt. per Pkg.	
K1154 Red	K1156 Blue		(In)	(mm)	(In)	(mm)	@70°F (20°C)	@122°F (50°C)	Reel	Coil	Reel	Coil
✓	✓	04	1/4	6.4	.500	12.7	300	150	500 ft.	100 ft.	44 lbs.	8 lbs.
✓	✓	05	5/16	7.9	.625	15.9	300	150	500 ft.	100 ft.	68 lbs.	13 lbs.
✓	✓	06	3/8	9.5	.625	15.9	300	150	500 ft.	100 ft.	56 lbs.	11 lbs.
✓	✓	08	1/2	12.7	.750	19.1	300	150	500 ft.	100 ft.	77 lbs.	14 lbs.
✓	✓	10	5/8	15.9	.895	22.6	200	100	300 ft.	100 ft.	60 lbs.	18 lbs.
✓	✓	12	3/4	19.1	1.030	26.2	200	75	300 ft.	100 ft.	72 lbs.	22 lbs.
✓	✓	16	1	25.4	1.313	33.3	150	75	300 ft.	100 ft.	105 lbs.	31 lbs.

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.