




- **Sales Tip:** *Ribs run the length of the mat. Rubber top resists exposure to sparks from welding.*
- **Where to Specify:** *Any work cell that requires added slip resistance.*

- Corrugated ribbed top surface of resilient SBR rubber is combined with dense closed cell foam base utilizing NOTRAX® exclusive UniFusion™ technology.
- UniFusion™ bond guaranteed for the life of the mat – See warranty for details
- Overall mat thickness is 1/2 inch.
- Sloped beveled foam on all 4 undersides affords easy access onto and off of mat.
- Custom widths available



RESULTS from INDEPENDENT TEST LABS & PRESENTED COMPARISONS to OTHER NOTRAX® INDUSTRIAL MATS



Black

**#474 ERGO MAT™**

<b>Stock Sizes</b>	<b>2' x 3'</b>	<b>3' x 5'</b>	<b>3' x 12'</b>	<b>Custom Widths</b>		
<b>List Price</b>	\$57.72	\$144.30	\$346.32	\$11.54/sq.ft.		
<b>Weight (lbs.)</b>	9	20	50	1.31/sq.ft.		
<b>Roll Sizes &amp; Custom Sizes</b>	<b>2' x 75'</b>	<b>3' x 75'</b>	<b>4' x 75'</b>	<b>2' Widths</b>	<b>3' Widths</b>	<b>4' Widths</b>
<b>List Price</b>	\$1443.00	\$2164.50	\$2886.00	\$9.62/sq.ft.	\$9.62/sq.ft.	\$9.62/sq.ft.
<b>Weight (lbs.)</b>	210	310	415	1.31/sq.ft.	1.31/sq.ft.	1.31/sq.ft.

Shipping Location: Superior Manufacturing Group - Moselle, MS 39459

\* For applications on carpeted, finished or polished surfaces, Mat Hold (090 – pg.59) is recommended to minimize mat movement

