



# SPIRALITE® 510

## PVC CLEAR TUBING

I.D.	O.D.	WALL THICKNESS	MAXIMUM W.P. AT 68°F	APPROX. WT. LBS/ROLL
1/8"	1/4"	1/16"	70	2.65
3/16"	5/16"	1/16"	70	3.07
1/4"	3/8"	1/16"	60	3.4
1/4"	7/16"	3/32"	60	5.38
1/4"	1/2"	1/8"	70	8.37
5/16"	7/16"	1/16"	50	4.63
5/16"	1/2"	3/32"	60	7.16
3/8"	1/2"	1/16"	50	5.58
3/8"	9/16"	3/32"	55	8.18
3/8"	5/8"	1/8"	60	11.55

I.D.	O.D.	WALL THICKNESS	MAXIMUM W.P. AT 68°F	APPROX. WT. LBS/ROLL
1/2"	5/8"	1/16"	40	7.39
1/2"	3/4"	1/8"	50	13.14
9/16"	7/8"	5/32"	45	18.73
5/8"	7/8"	1/8"	45	15.81
3/4"	1"	1/8"	35	18.6
7/8"	1-1/8"	1/8"	35	21.1
1"	1-1/4"	1/8"	30	23.8
1-1/4"	1-3/4"	1/4"	50	33.6
1-1/2"	2"	1/4"	40	42.9
2"	2-3/8"	3/16"	25	38.2

• **APPEARANCE/CONSTRUCTION:**

Clear PVC tube.

• **BENEFITS:**

- Non-toxic FDA formula.
- Colored tubing available with minimum orders.

• **GENERAL APPLICATIONS:**

- Water and light chemical transfer.
- Approved for use in USDA meat and poultry plants.

• **TEMPERATURE RANGE:**

-10°F to +130°F

• **STANDARD LENGTHS:**

1/8" thru 1"                      100ft.  
1-1/4" thru 2"                    50ft.



# SPIRALITE® 850

## "PAC-FLEX" PVC GRAY FLEXIBLE HOSE

• **APPEARANCE/CONSTRUCTION:**

Gray tube with white helix. Smooth cover and interior.

• **BENEFITS:**

- Manufactured to schedule 40 sizing specifications.
- Glues into standard PVC fittings.
- Meets or exceeds Western Underground Committee's 3.1 Specification, 3.2 Heat Distortion, 3.3 Impact Resistance, and 3.4 Conduit Stiffness.

• **GENERAL APPLICATIONS:**

- Cable conduit.
- Plumbing drain (no pressure) lines.

• **TEMPERATURE RANGE:**

-10°F to +130°F

• **STANDARD LENGTHS:**

1/2" thru 6"                      100ft.

NOMINAL SIZE	inch	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	6"
APPROX. O.D.	inch	.85	1.06	1.33	1.67	1.91	2.38	2.89	3.50	4.50	6.61
RECOM. MIN. BEND RADIUS AT 68°F*	inch	2	2	3	4	5	6	7	8	11	16
APPROX. WT.	lbs./ft.	.15	.23	.32	.40	.50	.70	.95	1.28	1.93	4.42

\* BEND RADIUS FOR CONTINUOUS SERVICE.