



# SPIRALITE® 2800

## EPDM RUBBER HOSE POLY-ETHYLENE/SOLID WIRE HELIX

### • APPEARANCE/CONSTRUCTION:

EPDM rubber tube with integrated solid wire with a poly-ethylene helix.  
Corrugated exterior, smooth interior wall.

### • BENEFITS:

- Wire helix resist deformation at higher temperatures.
- Good flexibility in higher temperature suction application.
- PVC reinforcement resist crushing.
- Polyethylene helix reduces drag.

### • GENERAL APPLICATIONS:

- Suction application in higher temperature conditions.
- Fly ash suction applications.
- Vacuum trucks.

### • TEMPERATURE RANGE:

-30°F to +220°F

### • STANDARD LENGTHS:

3" thru 6"                      100ft.  
8"                                      25ft.

NOMINAL SIZE	inch	3"	4"	5"	6"	8"
APPROX. O.D.	inch	3.57	4.69	5.81	6.82	8.56
RECOMMENDED W.P. AT 68°F	psi	30	29	28	28	25
RECOM. MIN. BEND RADIUS AT 68°F	inch	6	6	10	10	15
*APPROX. B.P. AT 68°F*	psi	100	90	85	85	75
APPROX. WT.	lbs./ft	1.45	2.20	3.25	3.91	5.20