



SPIRALITE® 4000

NBR RUBBER OIL AND GREASE SUCTION HOSE

- **APPEARANCE/CONSTRUCTION:**
Black NBR-blended rubber tube with white PVC helix.
Corrugated wall, smooth interior.
- **BENEFITS:**
 - Excellent oil resistance.
 - Lightweight and flexible.
- **GENERAL APPLICATIONS:**
 - Grease trap cleaning.
 - Oil suction and transfer.
- **TEMPERATURE RANGE:**
-30°F to +140°F
- **STANDARD LENGTHS:**
2" thru 4" 100ft.

NOMINAL SIZE	inch	2"	2.5"	3"	4"
APPROX. O.D.	inch	2.53	3.12	3.69	4.77
RECOMMENDED W.P. AT 68F	psi	60	50	50	45
VACUUM RATING AT 68F	in/HG	28	28	28	28
BEND RADIUS AT 68F	inch	9	11	12	17
APPROX. B.P. AT 68FS	psi	180	150	150	135
APPROX. WT.	lbs./ft	.87	1.02	1.61	2.30



SPIRALITE® 5000

PETROLEUM TANK DROP HOSE WITH STATIC WIRE

- This hose is engineered with a NBR tube & cover for the pressure, gravity flow or suction movement of gasoline and petroleum base products with an aromatic content not to exceed 50%.
- Spiralite 5000 is compounded especially to remain flexible to temperature readings of -30°F.
- Standard hose includes static conductive tube and copper static wire.
- Spiralite 5000 is manufactured to offer
 - Extra Durability and abrasion resistance.
 - High resistance to gasoline and natural elements such as ozone weather cracking.
 - Lightweight for ease of handling.
- See Banding Sleeve 5500 for drop hose
- See W187 for vapor recovery hose.



ID	OD	WP @ 72°F	BURST @ 72°F	BEND. RADIUS"	WEIGHT/FT.
2"	2.66	100	400	4	.87
2-1/2"	3.19	100	360	5	1.13
3"	3.76"	65	260	6	1.71
4"	4.79"	65	260	8	2.44

CONSTRUCTION: Tube-Black Synthetic Rubber
Reinforcement - Polyester and Static Wire
Cover - Yellow PVC Helix
Banding Sleeve - Black PVC

LENGTH: Spiralite 5000 Drop Hose —100'