



# SPIRALITE® W187

## CORRUGATED POLYURETHANE VAPOR RECOVERY HOSE WITH STATIC WIRE

- **APPEARANCE/CONSTRUCTION:**

Clear Polyurethane tube with Yellow PVC helix and static wire.

- **BENEFITS:**

- Lightweight and highly flexible.
- Resistant to chemical vapors and light abrasives.
- Static conductive wire.

- **GENERAL APPLICATIONS:**

- Vapor recovery for use with Spiralite 5000.
- Ducting dust and light abrasives.

- **TEMPERATURE RANGE:**

-30°F to +140°F

- **STANDARD LENGTHS:**

1-1/2" thru 6"                    100ft.  
8"                                        50ft.

- See 5600 for Vapor Recovery Banding Sleeve

NOMINAL SIZE	inch	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"
APPROX. O.D.	inch	1.88	2.43	2.96	3.54	4.56	5.51	6.52	8.75
RECOM. MIN. BEND RADIUS AT 68°F*	inch	1.5	2	2.5	3	4	5	6	10
APPROX. WT.	lbs./ft.	.36	.48	.61	.69	.92	1.13	1.24	2.42

\* BEND RADIUS FOR CONTINUOUS SERVICE.