

® SUN-FLOW SF-30



Code: SF-30 P.V.C. BRICK RED WATER DISCHARGE HOSE

NOMINAL SIZE	I.D.	APPROX. WALL	Max.W.P. at 70°F psi	DESIGN B.P. psi	APPROX. Wt. 300ft
1-1/2"	1.61"	0.075"	110 psi	360	66 lbs
2"	2.09"	0.075"	100 psi	320	87 lbs
3"	3.07"	0.079"	100 psi	300	129 lbs
4"	4.13"	0.083"	80 psi	240	181 lbs

- STND. LENGTH: 300 ft. per bale (Special order for longer lengths)
- TEMP. RANGE: -5°F to 170°F
- APPLICATIONS: Thick, tough wall for Rentals, Construction, Mines.
- CONSTRUCTION: 2 Polyester Spirals plus 1-ply vertical yarns.
- FLAME RESISTANT: **USMSHA IC-150/1 Special order only**
- CAUTION: For liability purposes, if temperature exceeds 110°F the working pressure will go down. Please check with factory to ensure sufficient safety factor.

® SUN-FLOW SF-30



Code: SF-30 P.V.C. 100 PSI RANGE BRICK RED DISCHARGE HOSE

NOMINAL SIZE	I.D.	APPROX. WALL	Max.W.P. at 70°F psi	DESIGN B.P. psi	APPROX. Wt. 300ft
6"	6.18"	0.118"	100	300	329 lbs

- LENGTH: 300 ft. per bale (Special order for longer lengths)
- TEMP. RANGE: -5°F to 170°F
- APPLICATIONS: Mines, Construction, etc.
- CONSTRUCTION: 3-Ply Polyester yarns. Both tube and cover are extruded simultaneously to obtain maximum bonding.
- CAUTION: For liability purposes, if temperature exceeds 110°F the working pressure will go down. Please check with factory to ensure sufficient safety factor.