



Flared Seal Plug 639F

Ref. SAE 010109



PART NO.	TUBE SIZE	STRAIGHT THREAD	C HEX	L
639F-4	1/4	7/16-20	7/16	.69
639F-5	5/16	1/2-20	1/2	.78
639F-6	3/8	5/8-18	5/8	.88
639F-8	1/2	3/4-16	3/4	1.06
639F-10	5/8	7/8-14	7/8	1.19



Cap Nut 640F

Ref. SAE 010112

PART NO.	TUBE SIZE	STRAIGHT THREAD	C HEX	L
640F-3*	3/16	3/8-24	1/2	.47
640F-4*	1/4	7/16-20	9/16	.53
640F-5*	5/16	1/2-20	5/8	.62
640F-6*	3/8	5/8-18	3/4	.69
640F-8*	1/2	3/4-16	7/8	.84
640F-10*	5/8	7/8-14	1-1/16	.97




*Should be used with 2GF copper gasket.

Flared Union—Female Flare to Female Flare 660FHD

Ref. SAE 010107

PART NO.	TUBE SIZE	STRAIGHT THREAD	C HEX	L	FLOW DIA. D
660FHD-4*	1/4	7/16-20	5/8	1.03	.250
660FHD-6*	3/8	5/8-18	13/16	1.26	.375
660FHD-8*	1/2	3/4-16	15/16	1.43	.500
660FHD-10*	5/8	7/8-14	1-1/16	1.69	.626





*Should be used with 2GF copper gasket.

Reducer—Male Flare to Female Flare 661FHD

Ref. SAE 010105

PART NO.	1 TUBE SIZE	2 TUBE SIZE	1 STRAIGHT THREAD	2 STRAIGHT THREAD	C HEX	L	FLOW DIA. D
661FHD-4-6*	1/4	3/8	7/16-20	5/8-18	13/16	1.20	.189
661FHD-4-8*	1/4	1/2	7/16-20	3/4-16	15/16	1.36	.189
661FHD-6-4*	3/8	1/4	5/8-18	7/16-20	5/8	1.10	.283
661FHD-6-8*	3/8	1/2	5/8-18	3/4-16	15/16	1.42	.283
661FHD-8-6*	1/2	3/8	3/4-16	5/8-18	13/16	1.39	.377
661FHD-8-10*	1/2	5/8	3/4-16	7/8-14	1-1/16	1.67	.408
661FHD-10-8*	5/8	1/2	7/8-14	3/4-16	15/16	1.60	.502
661FHD-10-12*	5/8	3/4	7/8-14	1-1/16-14	1-5/16	1.95	.502
661FHD-12-10*	3/4	5/8	1-1/16-14	7/8-14	1-1/16	1.86	.626



*Should be used with 2GF copper gasket.

Female Flare to Male Pipe Thread 664FHD

Ref. SAE 010106

PART NO.	TUBE SIZE	PIPE THREAD	STRAIGHT THREAD	C HEX	L	FLOW DIA. D
664FHD-4-2*	1/4	1/8	7/16-20	5/8	.91	.219
664FHD-4-4*	1/4	1/4	7/16-20	5/8	1.01	.250
664FHD-6-4*	3/8	1/4	5/8-18	13/16	1.28	.344
664FHD-8-6*	1/2	3/8	3/4-16	15/16	1.36	.406

*Should be used with 2GF copper flare gasket.

