



ISO Port Adapters

Advantages

To simplify the installation of hydraulic and pneumatic systems, Parker supplies a range of ISO Port Adapters for various sizes of metric threads and end configurations. These adapters include NPTF, flare, hose barb and NTA end configurations. Viton o-rings are standard on all ISO adapters.

Specifications

Meets dimensional requirements of ISO 6149-3 and SAE 2244-3.

Applications

Use with brass, copper or J844 type A & B nylon tubing. Manufactured for low and medium pressure line connection work.

Working Pressure and Temperature Ranges

Dependent on tubing or hose end connection

Nomenclature

Part numbers are constructed from symbols that identify the style and size of the fitting. The first series of numbers and letters identifies the style and type fitting. The second series of numbers describes the size.

Example:

1 59 F - 10 MI - 27

Forging (1) _____

45° Male Elbow _____

45° Flare _____

5/8" (10/16) Tube Size _____

MI-Metric ISO Port _____

27mm Port Thread _____

Special Fittings

Fitting configurations and / or sizes other than those shown in the catalog can be furnished. It is suggested that a print or sketch be submitted with the inquiry.

Pricing

Only items priced in current supplementary price list PL3501 are carried in stock. Price and delivery for non-stock items furnished on request for specified quantity.

E