

PLATINUM CURED SILICONE PRODUCTS

As a compliment to our successful Fluoropolymer and Sanitary Food Grade Hoses, PARKER/PAGE has expanded its hose and tubing line to include Platinum Cured Silicone Products. These high quality hoses continue our tradition of total customer satisfaction. PARKER/PAGE Fluoropolymer and Platinum Cured hoses meet or exceed the following requirements:

- FDA 21 CFR 177.1550, 177.2600
- UPS XXIII Class VI Requirements
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6 10, 11
- USDA Standards
- 3A Standards



Stainless Steel Braid PTFE Hoses with Extruded Platinum Cured Silicone Covers



NOTE: Uses SIL 300 Crimp Collar

See page 22 for Part Numbering System

SP

Platinum Cured Silicone Tubing

Part Number	Tube ID	Tube OD	Wall
Natural	Inch (MM)	Inch (MM)	Inch (MM)
SP-04X062	.250 (6.3)	.375 (9.5)	.062 (1.5)
SP-04X125	.250 (6.3)	.500 (12.7)	.125 (3.1)
SP-06X062	.375 (9.6)	.500 (12.7)	.062 (1.5)
SP-06X125	.375 (9.6)	.625 (15.9)	.125 (3.1)
SP-08X062	.500 (12.7)	.625 (15.9)	.062 (1.5)
SP-08X125	.500 (12.7)	.750 (19.0)	.125 (3.1)
SP-10X062	.625 (15.9)	.750 (19.0)	.062 (1.5)
SP-10X125	.625 (15.9)	.875 (22.2)	.125 (3.1)
SP-12X062	.750 (19.0)	.875 (22.2)	.062 (1.5)
SP-12X125	.750 (19.0)	1.000 (25.4)	.125 (3.1)
SP-14X062	.875 (22.2)	1.000 (25.4)	.062 (1.5)
SP-14X125	.875 (22.2)	1.125 (28.5)	.125 (3.1)
SP-16X062	1.000 (25.4)	1.125 (28.5)	.062 (1.5)
SP-16X125	1.000 (25.4)	1.250 (31.7)	.125 (3.1)

NOTE: Temperature Range:
-80°F to +450°F (-62°C to +232°C)
All ratings based on 72°F (22°C)

Smoothbore
PTFE Hose

Convuluted
PTFE Hose

Flare Seal
Hose

Silicone
Hose

Specialty
Hoses

Fittings

Accessories

Technical
Help

Warranty



Parker Hannifin, Parflex Division