## SIGHT FLOW INDICATORS

## **PSG - Sight Gauge Fluoropolymer**

PARKER/PAGE Sight Flow Indicators allow for visual inspection and continuous monitoring of flow, aeration, turbulence and cleanliness. The smooth, nonstick surface is easily cleaned, promotes minimal pressure drop, is unaffected by ultraviolet or sunlight and will not discolor in most applications. Sight Indicators are designed to perform in the highest purity applications over a broad temperature range.

PARKER/PAGE Sight Flow Indicators are manufactured from a safe, 100% fluoropolymer tube. The result is a light weight, sturdy product that is less susceptible to breakage. Assemblies can be supplied with a wide variety of 316 Stainless Steel high purity internal fitments. These include Sanitary, Flange, Instrumentation and many other industrial connectors which are readily available from PARKER/PAGE International.



Contact your
PARKER/PAGE Sales Rep
for Details at 1.800.847.7280
or by email page@parker.com

**PSB**Smoothbore PTFE Sight Flow

	Size	Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Burst Pressure
Part No.	Inches	Inch (MM)	Inch (MM)	Inch (MM)	PSI @ 72°F (Bars @ 22°C)	PSI @ 72°F (Bars @ 22°C)
08-PSG	1/2"	.500	.700	.100	200	800
		(12.7)	(17.7)	(2.5)	(13.8)	(55.2)
12-PSG	3/4"	.750	1.000	.125	175	700
		(19.0)	(25.4)	(3.2)	(12.1)	(48.3)
16-PSG	1"	1.000	1.250	.125	125	500
		(25.4)	(31.7)	(3.2)	(8.6)	(34.5)
24-PSG	1 ½"	1.500	1.750	.125	80	320
		(38.1)	(44.4)	(3.2)	(5.5)	(22.1)
32-PSG	2"	2.000	2.250	.125	65	260
		(50.8)	(57.1)	(3.2)	(4.9)	(17.9)
40-PSG	2 1/2"	2.500	2.800	.150	50	200
		(63.5)	(71.1)	(3.8)	(3.4)	(13.8)
48-PSG	3"	3.000	3.360	.180	40	160
		(76.2)	(85.3)	(4.6)	(2.8)	(11.0)
64-PSG	4"	4.000	4.420	.210	30	120
		(101.6)	(112.2)	(5.3)	(2.0)	(8.3)

NOTE: Temperature Range: -100°F to +400°F (-73°C to +204°C)

PARKER/PAGE Hose product materials are compliant with the following requirements: FDA 21 CFR 177.1550, 177.2600 • USP XXII Class Vi Requirements • Pharmacopoeia 3.1.9 • ISO 1093 Sections 5, 6, 10, 11 • USDA Standards • 3A Standards

GOODYEAR

Parker Hannifin, Parflex Division

Call Toll Free: 1-866-711-4673
WebSales@GoodyearRubberProducts.com

We Ship World Wide

Smoothbore PTFE Hose

Convoluted PTFE Hose

are Seal Hose

> llicone Hose

Specialty Hoses

ittings.

ccessories