

## PAGE-flex SBF™ HOSE ASSEMBLIES

### Smoothbore With Convoluted Hose Flexibility

PAGE-flex SBF™ utilizes a smoothbore PFA tube, a bonded, wire braid - silicone - textile braided composite, giving this product a superior bend radius, kink and vacuum resistance. This proprietary tube technology can then be additionally reinforced with any application specific braid for working pressure and abrasion resistance. The revolutionary design answers our customer's demands for a flexible smoothbore product utilizing the entire PARKER/PAGE International Hose line of standard fittings.

### PAGE-flex SBF™ Advantages

- Easily cleaned
- Very flexible
- PPIH full line of optional reinforcement types
- Standard - Stainless Steel reinforced
- -65°F to +325°F operating temperature range (dependent on reinforcement type)
- Cooler outside temperatures reduces operator burns
- Reduces environment temperatures in confined areas



**½ the minimum  
bend radius of  
conventional  
smoothbore  
products**

**PAGE-flex SBF™ is available in true bore sizes 3/8", 1/2", 3/4" and 1" with the complete line of standard PPIH crimp style fittings.**

**1 1/2" ALSO OFFERED VIA  
SPECIAL ORDER**

Smoothbore  
PTFE HoseConvoluted  
PTFE HoseFlare Seal  
HoseSilicone  
HoseSpecialty  
Hoses

Fittings

Accessories

Technical  
Help

Warranty



Parker Hannifin, Parflex Division

**GOODYEAR**  
RUBBER PRODUCTS INC.

Call Toll Free: **1-866-711-4673**

WebSales@GoodyearRubberProducts.com

**We Ship  
World Wide**