

PAGE-flex SBF™ HOSE SPECIFICATIONS

SBFW - Non-Conductive

SBFB - Conductive - Special Order Only

Part Number		Hose ID	Hose OD	Working Pressure	Minimum Burst Pressure	Vacuum Rating	Minimum Bend Radius
Non Conductive	Conductive	Inch (MM)	Inch (MM)	PSI @ 72°F (Bars @ 22°C)	PSI @ 72°F (Bars @ 22°C)	In. Hg. @ 72°F (Kg/Sq.CM @ 22°C)	Inches (MM)
06-SBFW	06-SBFB	0.375 (9.52)	0.625 (15.9)	300 (20.7)	1200 (82.7)	29.9 (1.0)	2.00 (50.8)
08-SBFW	08-SBFB	0.500 (12.7)	0.755 (19.2)	300 (20.7)	1200 (82.7)	29.9 (1.0)	2.50 (63.5)
12-SBFW	12-SBFB	0.750 (19.0)	1.040 (26.4)	250 (17.2)	1000 (69)	29.9 (1.0)	3.00 (76.2)
16-SBFW	16-SBFB	1.000 (25.4)	1.290 (32.8)	250 (17.2)	1000 (69)	29.9 (1.0)	4.00 (101.6)
24-SBFW	24-SBFB	1.500 (38.1)	1.850 (47.0)	200 (13.8)	800 (55.2)	29.9 (1.0)	7.00 (177.8)

NOTE: Temperature range: -65°F to +325°F (-54°C to +163°C). All ratings based upon 72°F (22°C).

Working pressures and vacuum ratings may vary depending upon end connections and process and temperature parameters. All dimensions nominal. Specifications are subject to change without notice.



Conductive and Non-Conductive Inner Tubing Available

Assemblies Only

Polypropylene, Kynar®, PEEK™ or Para-Aramid Assemblies

Smoothbore PTFE Hose

Convuluted PTFE Hose

Flare Seal Hose

Silicone Hose

Specialty Hoses

Fittings

Accessories

Technical Help

Warranty



Parker Hannifin, Parflex Division