

RUBBER COVERED FLUOROPOLYMER

Smoothbore with EPDM Rubber Cover



RCTW - NATURAL



RCTB - CONDUCTIVE

PARKER/PAGE International Rubber Covered Fluoropolymer hoses consist of an inner tube reinforced with multi-layered rubber, polyester cord and double helix wire for support. PARKER/PAGE hose can be grounded via it's internal helical wires and is available with a natural fluoropolymer or a conductive black static dissipative fluoropolymer inner core for applications where electrostatic dissipation is required. The wire helix supports full vacuum service in all areas.

STANDARD COLORS - Custom Colors available upon request

- Purple w/Silver Stripe.....1/2" - 4"
- Lt. Gray w/Silver Stripe.....1/2" - 2"
- Conductive ID - Purple w/Yellow Stripe....1/2" - 2"

RCTW (Natural) & RCTB (Conductive)

Part Number		Hose ID	Hose OD	Working Pressure	Minimum Burst Pressure	Vacuum Rating	Minimum Bend Radius	Weight
Natural	Conductive	Inch (MM)	Inch (MM)	PSI @ 72°F (Bars @ 22°C)	PSI @ 72°F (Bars @ 22°C)	In. Hg. @ 72°F (Kg/Sq.CM @ 22°C)	Inch (MM)	Lbs./Ft. (Kg/M)
08-RCTW	08-RCTB	0.500 (12.7)	0.950 (24.1)	500 (34.5)	2000 (138.0)	29.9 (1.0)	2.50 (63.5)	0.360 (0.535)
12-RCTW	12-RCTB	0.750 (19.0)	1.250 (31.7)	500 (34.5)	2000 (138.0)	29.9 (1.0)	3.00 (76.2)	0.550 (0.819)
16-RCTW	16-RCTB	1.000 (25.4)	1.530 (38.8)	450 (31.0)	1800 (124.2)	29.9 (1.0)	4.00 (101.6)	0.600 (0.892)
20-RCTW	20-RCTB	1.250 (31.7)	1.740 (41.2)	375 (25.9)	1500 (103.5)	29.9 (1.0)	7.00 (177.8)	0.930 (1.384)
24-RCTW	24-RCTB	1.500 (38.1)	2.130 (54.1)	375 (25.9)	1500 (103.5)	29.9 (1.0)	9.00 (228.6)	1.080 (1.607)
32-RCTW	32-RCTB	2.000 (50.8)	2.680 (68.0)	300 (20.7)	1200 (82.7)	29.9 (1.0)	10.50 (266.7)	1.330 (1.979)
40-RCTW	40-RCTB	2.500 (63.5)	3.300 (83.8)	200 (13.8)	1000 (69.0)	29.9 (1.0)	15.00 (381.0)	1.680 (2.500)
48-RCTW	48-RCTB	3.000 (76.2)	3.880 (98.6)	200 (13.8)	1000 (69.0)	29.9 (1.0)	18.00 (457.2)	2.020 (3.006)
64-RCTW	64-RCTB	4.000 (101.6)	4.980 (126.5)	150 (10.3)	750 (51.7)	29.9 (1.0)	22.5 (571.5)	2.830 (4.211)

NOTE: Temperature range: -40°F to +300°F (-40°C to +149°C). Decrease working pressure one percent for every 2°F above 212°F.

Note: Also available in Gray
 Note: Add -GRY to Suffix to Part Number
 EXAMPLE: 16-RCTW = Purple
 16-RCTW GRY = Gray

PARKER/PAGE Hose product materials are compliant the the following requirements: FDA 21 CFR 177.1550, 177.2600 • USP XXII Class VI Requirements • Pharmacopoeia 3.1.9 • ISO 1093 Sections 5, 6, 10, 11 • USDA Standards • 3A Standards

Smoothbore PTFE Hose
Convuluted PTFE Hose
Flare Seal Hose
Silicone Hose
Specialty Hoses
Fittings
Accessories
Technical Help
Warranty



Parker Hannifin, Parflex Division



Call Toll Free: 1-866-711-4673
 WebSales@GoodyearRubberProducts.com

We Ship World Wide