

Cross-Reference Guide

SPECIFICATION	PARKER SERIES #	PUROSIL #	FLEXFAB BLUE #	FLEXFAB GREEN #	FEDERAL #	FLEXTECH #
SAE J20R1 Class A Std.	6750, 6620	7030	5515	5500	5515	
SAE J20R1 Class A Hvy.	6751	70	5581	5501	5581	C40
SAE J20R2 Class A	6623		5508			
SAE J20R3 Class A Std.	6722	80	5526		5526	
SAE J20R3 Class A Hvy.	6723			5521		
SAE J20R5 Class A (CAC) Hot	6823	367				
SAE J20R5 Class A (CAC) Cold	6824	784				
Vacuum Tubing	6789	50				

Warning! This guide is intended to help users determine which hoses, as described by their various manufacturers, have been designed to perform similar functions. Care must be taken by the user to compare any variances in materials and construction between manufacturers, and to ensure the selected hose does not constitute a safety risk or change in required performance.



SAFETY WARNING

Failure to consider how temperature and other conditions affect hose performance could result in death, personal injury or property damage.

As temperature increases or decreases, burst pressure, safe working pressure, coupling retention properties, and other safety characteristics of the hose can significantly decrease. Deterioration due to wear, impulse, and other environmental conditions should also be considered. The user, through its own analysis and testing, is solely responsible for making the final selection of the hose and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met.



Parker Hannifin Corporation
Industrial Hose Division
Strongsville, OH

GOODYEAR
RUBBER PRODUCTS INC.

Call Toll Free: **1-866-711-4673**
WebSales@GoodyearRubberProducts.com

**We Ship
World Wide**