

HEATER & COOLANT HOSES

6722 X-treme Standard-Wall Heater Hose

Extruded heater hose that meets or exceeds SAEJ20R3 Class A specifications. This product is utilized as standard equipment on trucks, cars and buses. Since this product is extruded it can be offered in long lengths, which saves money by reducing scrap. These hoses are resistant to coolant solutions, cracking, ozone, cold leaks, peeling and aging.

TUBE COLOR: Brick Red

REINFORCEMENT: High-temperature-resistant plies

COVER COLOR: Blue

BRANDING: PARKER SILICONE SERIES 6722 -65° to +350°F (DATE CODE) MADE IN MEXICO

TEMP. RANGE: -65° to +350°F

APPLICATIONS: Heater hose for cars, trucks and buses

SPECIFICATIONS: SAEJ20R3, SAEJ2387

MAX. WORKING PRESSURE: 1/3 of the Burst Pressure



PART NUMBER	SIZE INCH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH FT	BURST PRESSURE PSI	WEIGHT LBS/100FT	BEND RADIUS	
		INCH	MM	INCH	MM				INCH	MM
6722-0250500	1/4	0.250	6	0.526	13	500	250	10.11	0.5	13
6722-0375500	3/8	0.375	10	0.690	18	500	250	13.16	0.8	19
6722-0500025	1/2	0.500	13	0.815	21	25	250	16.90	1.5	38
6722-0500050	1/2	0.500	13	0.815	21	50	250	16.90	1.5	38
6722-0500100	1/2	0.500	13	0.815	21	100	250	16.90	1.5	38
6722-0500500	1/2	0.500	13	0.815	21	500	250	16.90	1.5	38
6722-0625025	5/8	0.625	16	0.940	24	25	250	24.00	1.8	44
6722-0625050	5/8	0.625	16	0.940	24	50	250	24.00	1.8	44
6722-0625100	5/8	0.625	16	0.940	24	100	250	24.00	1.8	44
6722-0625250	5/8	0.625	16	0.940	24	250	250	24.00	1.8	44
6722-0750025	3/4	0.750	19	1.065	27	25	200	25.88	2.8	70
6722-0750050	3/4	0.750	19	1.065	27	50	200	25.88	2.8	70
6722-0750100	3/4	0.750	19	1.065	27	100	200	25.88	2.8	70
6722-0750250	3/4	0.750	19	1.065	27	250	200	25.88	2.8	70
6722-0875100	7/8	0.875	22	1.213	31	100	175	27.80	4.3	108
6722-1000025	1	1.000	25	1.339	34	25	175	33.98	5.0	127
6722-1000050	1	1.000	25	1.339	34	50	175	33.98	5.0	127
6722-1000100	1	1.000	25	1.339	34	100	175	33.98	5.0	127

Parker Hannifin Corporation
Industrial Hose Division
Strongsville, OH

