

## HEATER & COOLANT HOSES

# 6751 X-treme 4-Ply 20R1 Coolant Hose

Heavy-duty coolant hose that meets or exceeds SAEJ20R1 Class A specifications. This product is utilized for rugged automotive, heavy-duty equipment and marine-coolant applications. Since this product is mandrel made, it is offered in 3-foot lengths. These hoses are extremely durable and resistant to coolant solutions.

**TUBE COLOR:** Brick Red

**REINFORCEMENT:** High-temperature-resistant plies

**COVER COLOR:** Blue

**BRANDING:** PARKER SILICONE SERIES 6751 -65° to +350°F (DATE CODE) MADE IN MEXICO

**TEMP. RANGE:** -65° to +350°F

**APPLICATIONS:** Coolant hose for cars, trucks, buses and heavy equipment

**SPECIFICATIONS:** SAEJ20R1 Class A

**MAX. WORKING PRESSURE:** 1/3 of the Burst Pressure



PART NUMBER	SIZE INCH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH FT	BURST PRESSURE PSI	WEIGHT LB/FT
		INCH	MM	INCH	MM			
6751-0250003	1/4	0.250	6	0.630	16	3	477	0.50
6751-0313003	5/16	0.313	8	0.690	18	3	477	0.56
6751-0375003	3/8	0.375	10	0.760	19	3	477	0.69
6751-0500003	1/2	0.500	13	0.880	22	3	425	0.74
6751-0625003	5/8	0.625	16	1.010	26	3	376	0.86
6751-0750003	3/4	0.750	19	1.130	29	3	325	1.01
6751-0875003	7/8	0.875	22	1.260	32	3	325	1.11
6751-1000003	1	1.000	25	1.380	35	3	299	1.22
6751-1125003	1-1/8	1.125	29	1.510	38	3	299	1.38
6751-1250003	1-1/4	1.250	32	1.630	41	3	276	1.46
6751-1313003	1-5/16	1.313	33	1.690	43	3	276	1.55
6751-1375003	1-3/8	1.375	35	1.760	45	3	276	1.65
6751-1500003	1-1/2	1.500	38	1.880	48	3	249	1.83
6751-1625003	1-5/8	1.625	41	2.010	51	3	249	1.89
6751-1750003	1-3/4	1.750	44	2.130	54	3	225	1.95
6751-1875003	1-7/8	1.875	48	2.260	57	3	200	2.17
6751-2000003	2	2.000	51	2.380	60	3	200	2.28
6751-2125003	2-1/8	2.125	54	2.510	64	3	175	2.39
6751-2250003	2-1/4	2.250	57	2.630	67	3	175	2.46
6751-2313003	2-5/16	2.313	59	2.690	68	3	175	2.51
6751-2375003	2-3/8	2.375	60	2.760	70	3	175	2.58
6751-2500003	2-1/2	2.500	64	2.880	73	3	149	2.73
6751-2625003	2-5/8	2.625	67	3.010	76	3	125	2.88
6751-2750003	2-3/4	2.750	70	3.130	80	3	125	2.97
6751-2875003	2-7/8	2.875	73	3.260	83	3	87	3.11
6751-3000003	3	3.000	76	3.380	86	3	87	3.31
6751-3125003	3-1/8	3.125	79	3.510	89	3	75	3.38
6751-3250003	3-1/4	3.250	83	3.630	92	3	75	3.44
6751-3313003	3-5/16	3.313	84	3.690	94	3	75	3.47
6751-3375003	3-3/8	3.375	86	3.760	96	3	75	3.51
6751-3500003	3-1/2	3.500	89	3.880	99	3	75	3.60
6751-3625003	3-5/8	3.625	92	4.010	102	3	49	3.70
6751-3750003	3-3/4	3.750	95	4.130	105	3	49	3.81
6751-3875003	3-7/8	3.875	98	4.260	108	3	49	3.92
6751-4000003	4	4.000	102	4.380	111	3	49	4.04
6751-4250003	4-1/4	4.250	108	4.630	118	3	49	4.40
6751-4500003	4-1/2	4.500	114	4.880	124	3	49	4.70
6751-4750003	4-3/4	4.750	121	5.130	130	3	49	4.96
6751-5000003	5	5.000	127	5.380	137	3	49	5.20