

HOT AIR HOSES

6652 Inferno X-treme Plus FD SW Series

This FDA-approved softwall silicone hose is made for the delivery of hot air in high-performance, extreme-temperature applications that require food-grade, tasteless and odorless hose. The Inferno X-treme Plus FD is designed to convey hot air from the compressor to the storage tank in the transfer of dry bulk food commodities such as wheat, sugar or similar products.

TUBE COLOR: White

REINFORCEMENT: High-temperature-resistant plies

COVER COLOR: Blue

BRANDING: PARKER SILICONE SERIES 6652 -76° to +392°F (DATE CODE) MADE IN ITALY

TEMP. RANGE: -76° to +392°F

APPLICATIONS: Hot-air transfer in food industry

SPECIFICATIONS: USA FDA CFR 21 Part 177.2600, USA 3A Sanitary Standard Class II, ISO 1307-1997

MAX. WORKING PRESSURE: 1/3 of the Burst Pressure



PART NUMBER	SIZE INCH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH FT	BURST PRESSURE PSI	WEIGHT LBS/100FT	BEND RADIUS	
		INCH	MM	INCH	MM				INCH	MM
6652-2000130	2	2.008	51	2.559	65	130	450	82	6.3	160
6652-2000130H	2	2.008	51	2.717	69	130	450	119	9.8	250
6652-2750130	2-3/4	2.756	70	3.346	85	130	375	116	11.0	280
6652-3000130	3	2.992	76	3.661	93	130	330	159	13.0	330
6652-3000130H	3	2.992	76	3.780	96	130	330	187	14.2	360
6652-4000130	4	4.016	102	4.685	119	130	225	208	17.7	450

6653 Inferno X-treme Plus FD HW Series

This FDA-approved hardwall hose is made for the delivery of hot air in high-performance, extreme temperature applications that require food-grade, tasteless and odorless hose. The Inferno X-treme Plus FD is designed to convey hot air from the compressor to the storage tank in the transfer of dry bulk food commodities such as wheat, sugar or similar products.

TUBE COLOR: White

REINFORCEMENT: High-temperature-resistant plies with helical wires

COVER COLOR: Blue

BRANDING: PARKER SILICONE SERIES 6653 -76° to +392°F (DATE CODE) MADE IN ITALY

TEMP. RANGE: -76° to +392°F

APPLICATIONS: Hot-air transfer in food industry

SPECIFICATIONS: USA FDA CFR 21 Part 177.2600, USA 3A Sanitary Standard Class II, ISO 1307-1997

MAX. WORKING PRESSURE: 1/3 of the Burst Pressure



PART NUMBER	SIZE INCH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH FT	BURST PRESSURE PSI	WEIGHT LBS/100FT	BEND RADIUS	
		INCH	MM	INCH	MM				INCH	MM
6653-1500130	1-1/2	1.496	38	2.126	54	130	600	97	6.3	160
6653-2000130	2	2.008	51	2.638	67	130	450	124	9.8	250
6653-2500130	2-1/2	2.500	63.5	3.228	82	130	390	192	11.0	280
6653-2750130	2-3/4	2.756	70	3.346	85	130	375	208	13.0	330
6653-3000130	3	2.992	76	3.720	94.5	130	330	224	14.2	360
6653-4000130	4	4.016	102	4.744	120.5	130	225	306	17.7	450

Parker Hannifin Corporation
Industrial Hose Division
Strongsville, OH

