

# PROCO

STYLE

# 231/221

single wide arch spool type  
rubber expansion joints



Table 2: Sizes • Movements • Forces • Weights

See Notes Page 7

EXPANSION JOINT SIZE Nom. I.D. x Inch / (mm)	NEUTRAL LENGTH Inch / (mm)	EXPANSION JOINT STYLE	231 / 221 Movement Capability: From Neutral Position					Spring Rate Capability Based on 1" of Movement at Zero Pressure Conditions					Operating <sup>4</sup> Conditions			Weights <sup>5</sup> lbs / (kgs)		
			Axial Compression Inch / (mm)	Axial Extension Inch / (mm)	Lateral Deflection Inch / (mm)	Angular <sup>1</sup> Deflection Degrees	Torsional <sup>2</sup> Rotation Degrees	Force lbs per 1" rated Compression	Force lbs per 1" rated Extension	Force lbs per 1" rated Lateral Deflection	Force lb-inches per 1" rated Angular	Thrust Factor <sup>3</sup> Inz / (cmz)	Positive PSIG/ (Bar)	Vacuum Inches of Hg/ (mm of Hg)	Expansion Joint Assembly	Retaining Ring Set	Control <sup>6</sup> Rod Assembly	
1 1.25 1.5	(25)	6 (152)	231	1.2 (30)	0.6 (15)	0.6 (15)	50.4	2.0	U N D E R C U R R E N T T E S T I N G	5.12 (33)	200 (14.0)	26 (660)	2.0 (0.8)	2.0 (0.8)	2.3 (1.0)			
	(32)	6 (152)	231	1.2 (30)	0.6 (15)	0.6 (15)	43.1	2.0		6.20 (40)	200 (14.0)	26 (660)	2.5 (1.1)	2.5 (1.1)	2.3 (1.0)			
(40)	6 (152)	231	1.2 (30)	0.6 (15)	0.6 (15)	38.1	2.0	7.44 (48)		200 (14.0)	26 (660)	3.0 (1.4)	2.5 (1.1)	2.3 (1.0)				
2	(50)	6 (152)	231															
		7 (178)	231															
		8 (203)	231	1.4 (35)	0.7 (18)	0.6 (15)	34.2	2.0		12.40 (80)	200 (14.0)	26 (660)	4.0 (1.8)	4.0 (1.8)	2.8 (1.3)			
		9 (229)	231															
2.5	(65)	6 (152)	231															
		7 (178)	231															
		8 (203)	231	1.4 (35)	0.7 (18)	0.6 (15)	27.6	2.0		15.66 (101)	200 (14.0)	26 (660)	4.5 (2.0)	4.5 (2.0)	2.8 (1.3)			
		9 (229)	231															
3	(80)	6 (152)	231															
		7 (178)	231															
		8 (203)	231	1.4 (35)	0.7 (18)	0.6 (15)	23.0	2.0	19.38 (125)	200 (14.0)	26 (660)	5.5 (2.5)	5.5 (2.5)	2.8 (1.3)				
		9 (229)	231															
3.5	(90)	6 (152)	221															
		7 (178)	221															
		8 (203)	221	0.6 (15)	0.3 (8)	0.56 (14)	9.0	2.0	23.18 (150)	200 (14.0)	26 (660)	6.0 (2.7)	6.0 (2.7)	2.8 (1.3)				
		9 (229)	221															
4	(100)	6 (152)	231															
		7 (178)	231															
		8 (203)	231	1.4 (35)	0.7 (18)	0.6 (15)	18.8	2.0	27.90 (180)	200 (14.0)	26 (660)	8.0 (3.6)	8.0 (3.6)	2.8 (1.3)				
		9 (229)	231															
		10 (254)	231															
		12 (305)	231															

Series 231