

SERIES GG - 6201

Braided Flexible Metal Grooved Connectors (321 Stainless Steel Hose with 304 Stainless Braid and Grooved Ends or Grooved by Flange Ends).

TABLE 2: Sizes • Offset • Working Pressures • Weights

| Expansion Joint Size: ID X Length | Stock | Lateral Offset | | Working Press (PSI) | | Approx. Unit Ship Weight |
|-----------------------------------|-------|----------------|-----------|---------------------|--------|--------------------------|
| | | Intermittent | Permanent | @70°F | @300°F | |
| | | | | | | |
| 2 X 12 | S | 1/8" | 3/8" | 450 | 396 | 10 |
| 2 1/2 X 14 | S | 1/8" | 3/8" | 345 | 303 | 12 |
| 3 X 14 | S | 1/8" | 3/8" | 289 | 254 | 13 |
| 4 X 16 | S | 1/8" | 3/8" | 300 | 264 | 18 |
| 5 X 17 | S | 1/8" | 3/8" | 220 | 193 | 25 |
| 6 X 18 | S | 1/8" | 3/8" | 200 | 176 | 28 |
| 8 X 20 | S | 1/8" | 3/8" | 190 | 167 | 50 |
| 10 X 24 | S | 1/8" | 3/8" | 150 | 132 | 70 |
| 12 X 25 | S | 1/8" | 3/8" | 125 | 110 | 90 |

- NOTES:
1. Also comes in Grooved by Flange Design. Please specify series GF-6201
 2. Weight based on Series GF-6201
 3. "S" indicates stocked item.

