

SERIES TTS - 6201

PROCO
BRAIDED CONNECTORS


The Expansion Joint People

Braided Flexible Metal Threaded Connectors (321 Stainless Steel Hose with 304 Stainless Steel Braid and Male Carbon Steel Ends (NPT)).

TABLE 4: Sizes • Offset • Working Pressures • Weights

Expansion Joint Size: ID X Length	Stock	Lateral Offset		Working Press (PSI)		Approx. Unit Ship Weight
		Inter-mittent	Perm-anent	@70°F	@300°F	
1/2 X 6 1/2	S	1/4"	1/2"	1300	1144	1
1/2 X 9	X	1/4"	1/2"	1300	1144	1
1/2 X 10	S	1/4"	1/2"	1300	1144	1
3/4 X 7	S	1/4"	1/2"	880	774	1
3/4 X 10	S	1/4"	1/2"	880	774	1
3/4 X 11	X	1/4"	1/2"	880	774	1
1 X 8	S	1/4"	1/2"	605	532	1
1 X 10	S	1/4"	1/2"	605	532	1
1 1/4 X 8 1/2	S	1/4"	1/2"	605	532	1
1 1/4 X 10	S	1/4"	1/2"	570	501	1 1/2
1 1/4 X 11	X	1/4"	1/2"	570	501	1 1/2
1 1/4 X 12	X	1/4"	1/2"	570	501	2
1 1/4 X 13	S	1/4"	1/2"	570	501	2
1 1/2 X 9	S	1/4"	1/2"	570	501	1 1/2
1 1/2 X 12	S	1/4"	1/2"	525	462	1 1/2
1 1/2 X 14	X	1/4"	1/2"	525	462	2
2 X 10 1/2	S	1/4"	1/2"	455	400	2
2 X 12	S	1/4"	1/2"	455	400	2 1/2
2 X 14	S	1/4"	1/2"	455	400	3
2 X 15	S	1/4"	1/2"	455	400	3
2 1/2 X 12	S	1/4"	1/2"	345	303	5
2 1/2 X 14	S	1/4"	1/2"	345	303	5 1/2
2 1/2 X 16	S	1/4"	1/2"	345	303	6
3 X 14	S	1/4"	1/2"	290	255	8
3 X 16	S	1/4"	1/2"	290	255	9
3 X 17	X	1/4"	1/2"	290	255	10

NOTES: 1. "S" indicates stocked item.
2. "X" denotes 1-2 week shipment lead time.



Same Day Shipment

*At PROCO
Speed is our
Strength!*