



STYLE 100

## STYLE 100 COMPRESSED SHEET

**Color:** Green

A good quality general service manufactured from non-asbestos fibers and blended with a proprietary elastomeric compound. Style 100 is SEPCO's most economical alternative to compressed asbestos sheet. Recommended for applications up to 700°F and pressures up to 900 psi.

**Sizes:** 60" x 60"

**Thickness:** 1/64", 1/32", 1/16", 3/32", 1/8", 1/4".



STYLE 200

## STYLE 200 COMPRESSED SHEET/SBR BINDER

**Color:** Gray/Black

Manufactured from non-asbestos fibers bonded together into a homogenous sheet with an SBR binder. Our most popular compressed sheet. Withstands temperatures up to 750°F/400°C with excellent creep resistance and high torque retention properties. Treated with a clear anti-stick release agent. Recommended for pressures up to 1000 psi/69 bar. Applications include all mating pipe flanges, boilers, manhole and handhole gaskets, pumps, compressors, valves, turbines, mixers and vessels.

**Sizes:** 60" x 60"

**Thickness:** 1/64", 1/32", 1/16", 3/32", 1/8", 1/4".



STYLE 240

## STYLE 240 COMPRESSED SHEET/NEOPRENE BINDER

**Color:** Gray/Black

Manufactured from high quality non-asbestos fibers and bonded with neoprene rubber. It demonstrates outstanding resistance to the effects of hydrocarbons with a minimum of swelling. Popular in applications where hot oil handling equipment is used. Temperatures to 750°F/400°C. Pressures to 1000 psi/69 bar. Recommended for mating flanges, pumps, compressors, vessels, and where ever oil may cause excessive swelling with other rubber compounds.

**Sizes:** 60" x 60"

**Thickness:** 1/64", 1/32", 1/16", 3/32", 1/8", 1/4".



STYLE 300

## STYLE 300 COMPRESSED SHEET/SBR BINDER

**Color:** Off White

Manufactured from non-asbestos fibers and a SBR binder, and vulcanized to provide maximum strength and yield characteristics. Favored where color contamination of the product must be avoided. Maximum temperature limit is 750°F/400°C. Pressures to 1000 psi/69 bar. Recommended for all food handling and process equipment conveying products which must be kept uncontaminated from graphite and other discolorants.

**Sizes:** 60" x 120"

**Thickness:** 1/64", 1/32", 1/16", 3/32", 1/8", 1/4".