

HOW TO ORDER

Part No. S V 25 C 4 -4 F

Material	Body Type	Series	Coupling Half	Coupling Size	End Fitting Size	End Fitting Type	Seal Material	Sleeve Lock
S Stainless Steel 316	V Valved P** Plain (without valve)	25	C Coupler N Nipple	4=1/4" 8=1/2"	4=1/4" 6=3/8" 8=1/2"	F Female NPSF M Male NPT RP Female British Parallel BS2779	No letter Teflon -100°F to 350°F -73°C to 177°C KF* Kel F -400°F to 300°F -240°C to 149°C	SL

*Kel-F seal is installed in coupler only. Mating nipple supplied with Teflon only.

**Valved nipple/plain coupler combination will not activate valving in nipple. Single shut-off should be specified with valving in coupler half.

ACCESSORIES

SIZE	PRESSURE CAP	DUST CAP	DUST PLUG
1/4"	SPC25-4	SDC25-4	SDP25-4
1/2"	SPC25-8	SDC25-8	SDP25-8

! WARNING !

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND/OR PROPERTY DAMAGE.

This document and other information from Snap-tite, Inc., its subsidiaries and authorized distributors, provides product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operation conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met.

The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Snap-tite, Inc. and its subsidiaries at any time without notice.



ISO-9001 Certified