

# *Snap-tite* 56 Series – High Pressure Water Blast Coupling

*Featuring...Snap-tite quality with superior pressure and flow characteristics over the competition.*



- Engineered for operating pressures to 12,000 psi (828 bar) with 4:1 safety factor
- High strength steel construction with corrosion resistant yellow zinc dichromate plating
- Proven dog-lock mechanism provides safe positive connection and eliminates ball brinnelling
- Interchangeable with Parker WB Series and Aeroquip FD69 Series
- Sleeve guard aids in preventing accidental disconnection
- Straight through bore provides minimal pressure drop
- Sleeve lock increases safety by preventing accidental disconnection
- Available in 1/2" body size with 3/8" or 1/2" end fittings

*Snap-tite's 56 Series is designed for rugged, high-pressure water blasting equipment used in cleaning and paint stripping applications. Snap-tite has increased the working pressure to 12,000 psi (828 bar) while maintaining a 4:1 safety factor and interchangeability with competitive units. The 56 Series utilizes a proven dog-lock mechanism that increases surface contact and provides even load distribution under pressure thereby increasing the service life of the coupling.*

*In addition to cleaning and paint removal, water blast equipment is also used in the cleaning of maritime vessels as well as the removal of mill scale in industrial applications.*

<b>PRESSURE RATINGS</b>				
	<b>MAXIMUM WORKING</b>		<b>MINIMUM BURST</b>	
Size	psi	bar	psi	bar
1/2	12,000	828	48,000	3310