

# 60 Series — Parker 4000 Interchange

*Featuring...Snap-tite quality with superior pressure and flow characteristics over the competition*



- Interchangeable with Aeroquip FD42 and Parker 4000 Series
- 4:1 Safety factor
- Proven ball-lock mechanism provides positive connection
- Poppet style shut-off
- High strength steel construction
- Zinc yellow dichromate plating for corrosion resistance
- Choice of seal materials to handle a variety of fluids
- Sizes 1/4" & 3/8"

*Snap-tite's 60 Series is designed to accommodate high surge flows found in demanding hydraulic applications. Typical applications include snow plows, agricultural equipment and construction equipment. The 60 Series will interchange with Aeroquip's FD42 Series and Parker's 4000 Series. The 60 Series coupler is provided with a retaining groove for bulkhead mounting. The poppet style valve design provides excellent sealing in both high and low pressure applications. The 60 Series offers up to 3000 psi (210 bar) operating pressure in both the connected and disconnected positions.*

## PRESSURE RATINGS

SIZE	MAXIMUM WORKING		MINIMUM BURST		MAXIMUM CONNECT BY HAND	
	PSI	BAR	PSI	BAR	PSI	BAR
1/4"	3,000	210	12,000	830	150	10
3/8"	3,000	210	12,000	830	150	10