

# **76 Series — Hydraulic Couplings**

*Featuring...Snap-tite quality with higher working pressure and better flow performance than the competition.*



- High strength soft seat poppet valves insure zero leakage and higher flow rates than commonly used metal-to-metal sealing ball design.
- Heavy duty steel construction with yellow zinc dichromate plating for excellent corrosion resistance.
- Working pressures up to 14,500 psi (1,000 bar).
- Available in 1/4" and 3/8" sizes.

- The specially designed threaded sleeve has knurling at the front to facilitate connection by hand. The hex at the back allows connection with the use of a wrench.
- This coupling will interconnect with the Parker 3000 Series, Faster PVV Series, Perfecting 300 Series, Powerteam C38, Enerpac C-604, and other screw-to-connect couplings used in the hydraulic tool and rescue equipment markets.
- The couplers are available with male NPT, female NPSF, or female British parallel BS2779 end fittings. The nipples are available with female NPSF or female British parallel BS2779 end fittings. Other end fittings are available -- consult factory.

PERFORMANCE		
	1/4"	3/8"
Maximum Working Pressure (bar)	14,500 psi (1000)	14,500 psi (1000)
Minimum Burst Pressure (bar)	29,000 psi (2000)	29,000 psi (2000)
Torque to connect at 500 psi (35 bar)	20 in. lb. (0.23 kg.m.)	60 in. lb. (0.7 kg.m.)
Spillage upon disconnect at 15 psi (1 bar)	0.80 cc	0.95 cc