

Hose information is subject to change. For full details, visit our website or contact Customer Service.

7318 SOFT WALL FUEL FILL SAE 30R7

Style 7318 is often used as a fill neck hose. It can carry leaded, unleaded, oxygenated fuels with aromatics of up to 30%, gasohol and diesel fuel. Applications for this hose include: passenger cars, light trucks, boats and auxiliary fuel tanks on RV's. The rugged construction helps prevent hose collapse. This hose meets all the requirements of the 30R7 specification.



Resistance:

Branding:
 SAE 30R7 TYPE 7318 Size
 Made In USA Caution Statement

Cover Color: Black
Oil Resistance: High
Construction:
 Tube: NBR
 Cover: CR
 Reinforcement: Nylon screen
Temperature Range: -34°F to +257°F
 -37°C to +125°C
Packaging: 60 ft.
 Other lengths available – 5% cutting charge
 Contact customer service for minimum run requirements

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
16731815060▲	1-1/2	38.10	1.87	47.50	2	35	0.24	n/a	n/a	0.62	0.92
16731817560	1-3/4	44.45	2.15	54.61	2	35	0.24	n/a	n/a	0.71	1.06
16731818760▲	1-7/8	47.63	2.25	57.15	2	35	0.24	n/a	n/a	0.76	1.13
16731820060	2	50.80	2.39	60.71	2	35	0.24	n/a	n/a	0.80	1.19
16731822560▲	2-1/4	57.15	2.67	67.82	2	35	0.24	n/a	n/a	0.93	1.38
16731823760▲	2-3/8	60.33	2.79	70.87	2	35	0.24	n/a	n/a	0.98	1.46

▲ = Make To Order (MTO)
 n/a = Not Applicable

AUTOMOTIVE/MARINE COOLANT Automotive – Air Brake, Fuel, Heater & Coolant