

Hose information is subject to change. For full details, visit our website or contact Customer Service.

SAND AND CEMENT DISCHARGE – Black Cover

Sand and Cement Discharge is the right hose for cement and concrete placement and sand slurry discharge applications. This hose is available with two tube thicknesses (1/4" and 1/2") both of which are very abrasion resistant. The black SBR/EPDM cover is resistant to abrasion, moisture, weathering and aging. The 4 to 10 plies of reinforcement allow for a range of working pressures from 60 to 100 psi.



Cover Color: Black
Oil Resistance: Limited
Construction:
Tube: SBR - 1/4" or 1/2" thick
Cover: SBR/EPDM
Reinforcement: Wrapped construction with 4 to 10 plies of medium weight duck fabric
Temperature Range: -40°F to +160°F
 -40°C to +71°C
Packaging: 50 ft. lengths maximum
 Hand built – \$250.00 minimum order per size

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
11450025502▲	2-1/2	63.50	3.69	93.66	4	100	0.69	n/a	n/a	3.80	5.66
11450030502▲	3	76.20	4.19	106.36	4	100	0.69	n/a	n/a	4.40	6.55
11450040502▲	4	101.60	5.19	131.76	4	75	0.52	n/a	n/a	5.60	8.33
11450050502▲	5	127.00	6.81	173.04	5	75	0.52	n/a	n/a	10.20	15.18
11450060502▲	6	152.40	7.81	198.44	5	75	0.52	n/a	n/a	11.90	17.71
11450080502▲	8	203.20	9.88	250.83	6	60	0.41	n/a	n/a	16.30	24.26
11450100502▲	10	254.00	12.13	307.98	8	60	0.41	n/a	n/a	23.90	35.57
11450120502▲	12	304.80	14.25	361.95	10	60	0.41	n/a	n/a	28.00	41.67

▲ = Make To Order (MTO)
 n/a = Not Applicable

TRANSPORTER® HOT AIR BLOWER

Transporter Hot Air Blower hose is designed to handle air supply service up to 150 psi. This hose is also used for the transferring of hot air to tanks on dry bulk material trucks. This hose features an EPDM tube and cover which offers excellent heat resistance. The EPDM cover also stands up to the effects of ozone and weathering. This construction resists customary transport conditions. This hose is rated at **full vacuum**.



Cover Color: Brown
Oil Resistance: Limited
Construction:
Tube: EPDM
Cover: EPDM
Reinforcement: Spiral steel wire helix(es) between synthetic textile plies
Temperature Range: -30°F to +350°F
 -34 C to +177°C
Packaging: 100 ft. maximum

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17717025002▲	2-1/2	63.50	3.06	77.79	2	150	1.03	12.50	317.50	1.70	2.53
17717030002	3	76.20	3.56	90.49	2	150	1.03	15.00	381.00	2.00	2.98
17717040002	4	101.60	4.63	117.48	2	150	1.03	18.00	457.20	2.80	4.17

▲ = Make To Order (MTO)

MATERIAL HANDLING