

TYPE 924 PETROLEUM TRANSFER

Type 924 Petroleum Transfer hose is perfect for those applications for the bulk transfer of petroleum products. This hose can also be used to handle most hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. The black NBR tube has excellent resistance to oil. The cover compound of NBR/PVC is both oil and abrasion resistant. This hose is rated at **full vacuum**.



- Cover Color:** Black
- Oil Resistance:** High
- Construction:**
 - Tube:** NBR, RMA Class A
 - Cover:** NBR/PVC, RMA Class B
 - Reinforcement:** Spiral steel wire helix(es) between synthetic textile plies
- Temperature Range:** -30°F to +200°F
-34°C to +93°C
- Packaging:** 100 ft. maximum

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17812008002	1	25.40	1.50	38.10	2	200	1.38	2.50	63.50	0.50	0.74
17812010002	1-1/4	31.75	1.75	44.45	2	200	1.38	3.00	76.20	0.70	1.04
17812015002	1-1/2	38.10	2.00	50.80	2	150	1.03	4.50	114.30	0.80	1.19
17812020002	2	50.80	2.47	62.71	2	150	1.03	6.00	152.40	1.00	1.49
17812025002	2-1/2	63.50	3.06	77.79	2	150	1.03	7.50	190.50	1.50	2.23
17812030002	3	76.20	3.56	90.49	2	150	1.03	9.00	228.60	1.70	2.53
17812040002	4	101.60	4.63	117.48	2	150	1.03	12.00	304.80	2.50	3.72
17812060002▲	6	152.40	6.75	171.45	2	100	0.69	30.00	762.00	5.00	7.44

▲ = Make To Order (MTO)