

LW701 HEAVY DUTY FIRE ENGINE SUCTION HOSE

- Premium quality, heavy duty fire engine suction hose designed for remote water removal and hydrant connections on fire trucks.
- Rugged cover design provides excellent abrasion and ozone resistance.

Tube: SBR.
Reinforcement: Textile with steel wire helix.
Cover: SBR.
Temperature: -40° to +180°F.

Meets or exceeds NFPA #1962 and #1901 requirements.



I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
2 1/2"	3 1/8"	15"	150	1.60	Full
3"	3 5/8"	18"	150	1.97	Full
3 1/2"	4 1/8"	21"	150	2.27	Full
4"	4 5/8"	24"	150	2.72	Full
4 1/2"	5 1/8"	27"	150	3.70	Full
5"	5 3/4"	30"	150	5.00	Full
6"	6 3/4"	36"	150	5.93	Full

LW720 CORRUGATED FIRE ENGINE SUCTION HOSE

- Corrugated fire engine suction hose designed for remote water removal and hydrant connections on fire trucks.
- Rugged SBR cover provides excellent abrasion and ozone resistance.

Tube: SBR.
Reinforcement: Textile with steel wire helix.
Cover: Corrugated SBR.
Temperature: -40° to +180°F.

Meets or exceeds NFPA #1962 and #1901 requirements.



I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
2 1/2"	3"	15"	150	1.37	Full
3"	3 1/2"	18"	150	1.68	Full
4"	4 1/2"	24"	150	2.23	Full
4 1/2"	5 1/8"	27"	150	3.03	Full
5"	5 11/16"	30"	150	4.02	Full
6"	6 11/16"	36"	150	4.77	Full
6"	6 3/4"	24"	100	6.24	Full