

SW309 PETROVAC PETROLEUM SUCTION HOSE



- Lightweight suction and discharge hose for transferring petroleum products.
- Dual wire helix construction provides full vacuum capabilities.
- Tube and cover are ozone, abrasion, and oil resistant.

Tube: Extruded specially compounded Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Specially compounded Nitrile.
Temperature: -40° to +180°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1"	1 ⁷ / ₁₆ "	4"	150	.42	Full
1 ¹ / ₄ "	1 ¹¹ / ₁₆ "	5"	150	.50	Full
1 ¹ / ₂ "	1 ¹⁵ / ₁₆ "	6"	150	.63	Full
2"	2 ¹ / ₂ "	8"	150	.98	Full
2 ¹ / ₂ "	3"	10"	150	1.24	Full
3"	3 ¹ / ₂ "	12"	150	1.70	Full
4"	4 ⁹ / ₁₆ "	18"	150	2.45	Full
5"	5 ³ / ₄ "	25"	100	3.61	Full
6"	6 ³ / ₄ "	30"	100	4.78	Full

SW327 HOT TAR & ASPHALT HOSE - VAMAC® TUBE

Caution: Do not use above 350°F. or for other services.
 Refer to SW387 (page 60) for intermittent service applications.



- Ultra-high temperature hose designed for hot tar, hot oil and unrefined petroleum products.
- Premium grade tube and cover provide heat and abrasion resistance.

Tube: Extruded heat resistant Vamac®.
Reinforcement: Textile with wire helix.
Cover: Extruded heat resistant Vamac®.
Temperature: -40° to +350°F. (Continuous service).

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1 ¹ / ₂ "	2 ¹ / ₁₆ "	6"	150	.92	Full
2"	2 ¹⁹ / ₃₂ "	8"	150	1.36	Full
2 ¹ / ₂ "	3 ¹ / ₈ "	10"	150	1.87	Full
3"	3 ²¹ / ₃₂ "	12"	150	2.50	Full
4"	4 ³ / ₄ "	16"	150	3.57	Full

Vamac® is a registered trademark of DuPont

SW333 PETROLEUM SUCTION HOSE

Caution: Not for dock hose service.



- High pressure petroleum suction and discharge hose designed for bottom loading of tank trucks and rail cars.
- Cover is oil, abrasion and ozone resistant.

Tube: Extruded Nitrile.
Reinforcement: Textile with wire helix.
Cover: Specially compounded Nitrile.
Temperature: -40° to +180°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
2"	2 ⁹ / ₁₆ "	8"	250	1.22	Full
3"	3 ³ / ₄ "	12"	250	2.29	Full
4"	4 ³ / ₄ "	18"	250	3.28	Full
6"	6 ²⁹ / ₃₂ "	30"	250	5.69	Full