

## SWC509 TITANFLEX® ULTRAVAC OIL FIELD VACUUM HOSE

- Ultra-flexible oil field vacuum hose ideal for transferring diluted industrial chemicals, petroleum waste, sludge, slurry, and sediments.
- Lightweight corrugated design is easy to lift, drag, and maneuver.

**Tube:** Extruded specially compounded Nitrile.  
**Reinforcement:** Textile with dual wire helix.  
**Cover:** Corrugated SBR.  
**Temperature:** -40° to +160°F.

Not recommended for refined petroleum products with over 35% aromatics.



I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1"	1 1/2"	1"	250	.48	Full
1 1/2"	2 1/16"	1 1/2"	250	.72	Full
2"	2 9/16"	2"	250	.93	Full
2 1/2"	3 1/8"	2 1/2"	200	1.40	Full
3"	3 5/8"	3"	200	1.66	Full
4"	4 5/8"	4"	150	2.23	Full
6"	6 3/4"	10"	125	4.02	Full

## SWC609 TITANFLEX® PETROLEUM SUCTION HOSE - BLACK COVER

- Corrugated petroleum suction and discharge hose designed for commercial gasoline, diesel and fuel oils.
- Extreme flexibility and superior bend radius.
- Unique non-kinking design increases service life.

**Tube:** Extruded Nitrile.  
**Reinforcement:** Textile with dual wire helix.  
**Cover:** Specially compounded Nitrile (Black or Red).  
**Temperature:** -40° to +180°F.



I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1 1/2"	2 1/16"	1 1/2"	250	.72	Full
2"	2 9/16"	2"	250	.92	Full
2 1/2"	3 3/16"	2 1/2"	200	1.35	Full
3"	3 11/16"	3"	200	1.66	Full
4"	4 5/8"	4"	150	2.26	Full
6"	6 3/4"	8"	125	4.16	Full

## SWC609R TITANFLEX® PETROLEUM SUCTION - RED CVR

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1 1/2"	2 1/16"	1 1/2"	250	.72	Full
2"	2 9/16"	2"	250	.95	Full
2 1/2"	3 3/16"	2 1/2"	200	1.35	Full
3"	3 11/16"	3"	200	1.70	Full
4"	4 5/8"	4"	150	2.32	Full
6"	6 3/4"	8"	125	4.10	Full

