

SS115 LIGHTWEIGHT WATER DISCHARGE HOSE

- Economically designed water discharge hose for construction and light duty industrial applications.
- Durable cover offers protection against outdoor elements.

Tube: SBR.
Reinforcement: Textile.
Cover: SBR.
Temperature: -40° to +180°F.



I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
1 1/2"	1 5/16"	2 plies	100	.43
2"	2 7/16"	2 plies	100	.54
2 1/2"	2 7/8"	2 plies	100	.67
3"	3 7/16"	2 plies	100	.80
3 1/2"	3 15/16"	2 plies	100	.94
4"	4 7/16"	2 plies	100	1.07
4 1/2"	4 15/16"	2 plies	100	1.21
5"	5 7/16"	2 plies	100	1.33
5 9/16"	6"	2 plies	75	1.46
6"	6 7/16"	2 plies	75	1.60
6 5/8"	7 1/16"	2 plies	75	1.74
8"	8 9/16"	4 plies	75	2.99

ES115 LIGHTWEIGHT WATER DISCHARGE HOSE

Custom Made Hose Product

I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
8"	8 1/2"	2 plies	100	3.90
8 5/8"	9 1/8"	2 plies	100	4.30
10"	10 17/32"	2 plies	100	5.00
10 3/4"	11 5/16"	2 plies	75	5.30
12"	12 17/32"	2 plies	75	6.00
12 3/4"	13 5/16"	2 plies	75	6.40
14"	14 17/32"	2 plies	75	7.00
16"	16 17/32"	2 plies	50	7.90
18"	18 17/32"	2 plies	50	8.90

SS122 LIGHTWEIGHT WATER JETTING HOSE

- Lightweight water jetting hose for washdown and offshore jetting applications.
- Premium grade cover protects against outdoor elements.

Tube: Extruded SBR.
Reinforcement: Textile.
Cover: SBR.
Temperature: -40° to +180°F.



I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
1 1/4"	1 11/16"	2 plies	500	.49
1 1/2"	1 15/16"	2 plies	500	.60
2"	2 1/2"	2 plies	500	.96
2 1/2"	3"	2 plies	500	1.15
3"	3 1/2"	2 plies	500	1.36
4"	4 1/2"	2 plies	300	1.75