

SW300 LIGHTWEIGHT WATER SUCTION

- Lightweight water suction hose designed for construction and industrial washdown applications.
- Wire reinforcement provides full vacuum capabilities without sacrificing flexibility.
- Abrasion resistant cover protects against ozone attack.

Tube: SBR.
Reinforcement: Textile with wire helix.
Cover: SBR.
Temperature: -40° to +180°F.



I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
6"	6 ⁵ / ₈ "	30"	100	3.64	Full
8"	9 ³ / ₁₆ "	48"	100	10.88	Full

EW300 LIGHTWEIGHT WATER SUCTION - 2 PLY

Custom Made Hose Product

- Lightweight 2 ply water suction hose for construction and industrial washdown applications.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
6 ⁵ / ₈ "	7 ¹ / ₂ "	40"	125	5.90	Full
7"	7 ⁷ / ₈ "	42"	125	7.00	Full
7 ¹ / ₂ "	8 ³ / ₈ "	45"	125	7.50	Full
8"	8 ⁷ / ₈ "	48"	100	8.40	Full
8 ⁵ / ₈ "	9 ⁵ / ₈ "	52"	100	10.60	Full
10"	10 ³¹ / ₃₂ "	60"	100	13.00	Full
10 ³ / ₄ "	11 ²⁷ / ₃₂ "	65"	75	17.20	Full
12"	13 ¹ / ₈ "	72"	75	18.00	Full
12 ³ / ₄ "	13 ⁷ / ₈ "	77"	75	22.00	Full
14"	15 ¹ / ₈ "	84"	75	24.00	Full
16"	17 ¹ / ₈ "	96"	50	27.30	Full
18"	19 ¹ / ₈ "	108"	50	30.60	Full

EW301 HEAVY DUTY WATER SUCTION - 4 PLY

Custom Made Hose Product

- Heavy duty 4 ply water suction hose for mining, construction, and other industrial applications.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
8"	9 ¹ / ₈ "	48"	150	10.90	Full
8 ⁵ / ₈ "	9 ³ / ₄ "	56"	150	11.70	Full
10"	11 ¹ / ₈ "	60"	150	14.50	Full
10 ³ / ₄ "	12"	68"	150	18.80	Full
12"	13 ⁵ / ₁₆ "	72"	150	20.90	Full
12 ³ / ₄ "	14"	80"	150	22.10	Full
14"	15 ⁵ / ₁₆ "	84"	125	26.10	Full
16"	17 ⁵ / ₁₆ "	96"	125	29.60	Full
18"	19 ⁵ / ₁₆ "	108"	100	33.20	Full